

## SMS RELÆ GSM PRO2 MED MODULER FOR DIGITAL/ANALOG INPUT/OUTPUT

16454.2

- Mulighed for GPS overvågning/rapportering
- Mulighed for ekstern antenne
- Konfigureres via PC eller App




### PRODUKTBESKRIVELSE

### SPECIFIKATIONER

|                                                    |                                                                                 |
|----------------------------------------------------|---------------------------------------------------------------------------------|
| <b>2G</b>                                          | Quad-band GSM bands: 850, 900, 1800 and 1900 MHz                                |
| <b>3G</b>                                          | Five-band UMTS (WCDMA/FDD) bands: 800, 850, 900, 1800, 1900 and 2100 MHz        |
| <b>4G</b>                                          | LTE CAT1: Penta band 700 (Bd28)/ 800 (Bd20)/900 (Bd8)/1800 (Bd3)/2100 MHz (Bd1) |
| <b>Afisoleringslængde</b>                          | 6 mm                                                                            |
| <b>Antenna GSM</b>                                 | 50 Ohm, SMA-plug                                                                |
| <b>Bredde</b>                                      | 36 mm                                                                           |
| <b>Bus protocol / interface</b>                    | Modbus RTU / RS485, half-duplex, non-insulated                                  |
| <b>Connection type</b>                             | Skrue                                                                           |
| <b>Contact material</b>                            | AgNi 90/10                                                                      |
| <b>Continuous current max / Inrush current max</b> | 5 / 5 A                                                                         |
| <b>Counter input (pull-down)</b>                   | 1000 pulses/s max. Pulldown res. 24 kOhm                                        |
| <b>Current consumption</b>                         | 275 mA @ 24V dc                                                                 |
| <b>DIN-VDE Spec</b>                                | LVD 2014/35/EC, EN 50178. EMC 2014/30/EC, EN 61326-1                            |
| <b>Electrical life in hours (AC1)</b>              | 1,5x10 <sup>5</sup>                                                             |
| <b>Electromagnetic Compatibility</b>               | EN55011, EN61326-1                                                              |

|                                        |                                |
|----------------------------------------|--------------------------------|
| <b>Forsyningsspænding</b>              | 10-30V dc                      |
| <b>Frequency spectrum</b>              | ETSI EN 301-511 V9.0.2         |
| <b>Højde</b>                           | 77 mm                          |
| <b>Input resistance U / I</b>          | 80K / 500Ω                     |
| <b>Input signal U / I max</b>          | 30 V / -                       |
| <b>IP-klasse</b>                       | IP20                           |
| <b>Længde</b>                          | 88 mm                          |
| <b>Mechanical life hours</b>           | 15x10 <sup>6</sup>             |
| <b>Minimum pulse duration</b>          | 500 ms                         |
| <b>Montage</b>                         | TS 35/7,5 og direkte montering |
| <b>Number of ext. modules max</b>      | 15 pc                          |
| <b>Number of inputs</b>                | 2                              |
| <b>Number of outputs</b>               | 1                              |
| <b>Oprindelsesland</b>                 | NL                             |
| <b>Pakningsstørrelse</b>               | 1 pc                           |
| <b>Rated V ac / switching V ac max</b> | 250 / 250 V ac                 |
| <b>Relative humidity max</b>           | 80 %                           |
| <b>Relay contact</b>                   | 1 CO                           |
| <b>Resolution I (0-20 mA)</b>          | 40 µA / ± (40 µ + 0,3%)        |
| <b>Resolution U (0-10 V dc)</b>        | 20mV / ±(20mV+0,3%)            |
| <b>SIM card</b>                        | Nano-SIM                       |
| <b>Switching capacity max</b>          | 1200 VA                        |
| <b>Tariff code</b>                     | 85176990                       |
| <b>Temperaturområde drift fra</b>      | -20 °C                         |
| <b>Temperaturområde drift til</b>      | 60 °C                          |
| <b>Threshold digital inputs</b>        | Low <3, High >6V               |
| <b>Torque</b>                          | 0,4 Nm                         |
| <b>Tværsnit enkelt ledning fra</b>     | 0,2 mm <sup>2</sup>            |
| <b>Tværsnit enkelt ledning til</b>     | 4 mm <sup>2</sup>              |
| <b>Vægt</b>                            | 149 g                          |



LOGIN

REGISTER

Conta-SuperVision

Dashboard Name\*

Password\*

🗖

Forgot Password?

LOGIN