

SHS20V1SS	30	44	79	32	36	M5X5	59	8	25.4	6.5	12	20	12	16.5	60	6*9.5*8.5
SHS20LV1SS			98		50		78									
SHS25V1SS	36	48	92	35	35	M6X6.5	71	8	30.2	7.5	12	23	12.5	20	60	7*11*9
SHS25LV1SS			109		50		88									
SHS30V1SS	42	60	106	40	40	M8X8	80	8	35	8	12	28	16	23	80	9*14*12
SHS30LV1SS			131		60		105									
SHS35V1SS	48	70	122	50	50	M8X10	93	14.7	40.5	8	12	34	18	26	80	9*14*12
SHS35LV1SS			152		72		123									
SHS45V1SS	60	86	140	60	60	M10X15	106	14.9	51.1	10.5	16	45	20.5	32	105	14*20*17
SHS45LV1SS			174		80		140									
SHS55V1SS	70	100	171	75	75	M12X15	131	19.4	57.3	11	16	53	23.5	38	120	16*23*20
SHS55LV1SS			213		95		173									
SHS65V1SS	90	126	221	76	70	M16X20	175	19.5	71	19	16	63	31.5	53	150	18*26*22
SHS65LV1SS			272		120		226									

SHS-R/LR

--

Tekniske data

Type	Belastning kN		Max. statisk moment kNm					Vægt	
	C (dyn)	C(stat)	M _A		M _B		M _C	Vogn (kg)	Skinne (kg/m)
			1 vogn	2 vogn	1 vogn	2 vogn			
SHS15R	14.2	24.2	0.175	0.898	0.175	0.898	0.16	0.22	1.3
SHS25R	31.7	52.4	0.566	2.75	0.566	2.75	0.563	0.66	3.2
SHS25LR	36.8	64.7	0.848	3.98	0.848	3.98	0.696	0.8	
SHS30R	44.8	66.6	0.786	4.08	0.786	4.08	0.865	1.04	4.5
SHS30LR	54.2	88.8	1.36	6.6	1.36	6.6	1.15	1.36	
SHS35R	62.3	96.6	1.38	6.76	1.38	6.76	1.53	1.8	6.2
SHS35LR	72.9	127	2.34	10.9	2.34	10.9	2.01	2.34	
SHS45R	82.8	126	2.05	10.1	2.05	10.1	2.68	3.24	10.4
SHS45LR	100	166	3.46	16.3	3.46	16.3	3.53	4.19	
SHS55R	128	197	3.96	19.3	3.96	19.3	4.9	5.05	14.5
SHS55LR	161	259	6.68	31.1	6.68	31.1	6.44	6.57	

Standardlængder(L₀)	160	220	220	280	280	570	780	1270	
	220	280	280	360	360	675	900	1570	
	280	340	340	440	440	780	1020	2020	
	340	400	400	520	520	885	1140	2620	
	400	460	460	600	600	990	1260		
	460	520	520	680	680	1095	1380		
	520	580	580	760	760	1200	1500		
	580	640	640	840	840	1305	1620		
	640	700	700	920	920	1410	1740		
	700	760	760	1000	1000	1515	1860		
	760	820	820	1080	1080	1620	1980		
	820	940	940	1160	1160	1725	2100		
	940	1000	1000	1240	1240	1830	2220		
	1000	1060	1060	1320	1320	1935	2340		
	1060	1120	1120	1400	1400	2040	2460		
	1120	1180	1180	1480	1480	2145	2580		
	1180	1240	1240	1560	1560	2250	2700		
	1240	1360	1300	1640	1640	2355	2820		
	1360	1480	1360	1720	1720	2460	2940		
	1480	1600	1420	1800	1800	2565	3060		
	1600	1720	1480	1880	1880	2670			
			1840	1960	1960	2775			
			1960	2040	2040	2880			
			2080	2200	2200	2985			
			2200	2360	2360	3090			
				1960	2520	2520			
			2080	2680	2680				
			2200	2840	2840				
			2320	3000	3000				
		2440							
F	60	60	60	80	80	105	120	150	
G	20	20	20	20	20	22.5	30	35	
Max. længde	2500	3000	3000	3000	3000	3090	3060	3000	

Best.nr.

For bestillingsnumre kontakt venligst OEM Automatic Klitsø, EI afd.

SPECIFIKATIONER

Bredde	34 mm
Dynamic load	14,2 kN
Højde	24 mm
Længde	64,4 mm
Static load	24,2 kN