

EFFEPI RUSTFRI STÅL KUGLEVENTILER TYPE \"AL\" AISI 304

EFFAL10DA

Kemi rustfri stål kugleventil DN10 double acting
AISI304

- Materiale: Rustfri stål AISI 304
- Medier: Gas, Olie, Væske
- Størrelser: DN10 - DN100 (DA) DN10 - DN50 (SA)
- Fås med pneumatisk aktuator
- Temperaturområde: -15°C - +100°C



PRODUKTBESKRIVELSE

Rustfri stål kugleventil med roterende pneumatisk aktuator.

Ventilkrop: Rustfri stål AISI304

Kugle: Rustfri stål AISI304

Pakning: Virgin PTFE

Temperaturområder:

-15°C - +100°C

Max temperatur for special brug (med fuldt åben ventil):

+100°C brændstofs olier, mineral olier og mageriner

+90°C hav og drikkevand

+60°C trichlorethylen, butan, methan, propan, carbon dioxide

+40°C Alkohol, benzin, lette gasser, naturlige gasser, lime vand, sodavand.

Aktuator tryk:

Double acting fra 3 - 8 bar

Single acting fra 6 - 8 bar

Tilslutninger med GAS ISO228 hun-hun fittings.

Kan leveres med NPT eller DIN tilslutning

GAS tilslutning 1/8"

DA: 3/8" - 1/2" - 3/4" - 1" - 1 1/4" - 1 1/2" - 2" - 2 1/2" - 3" - 4" (double acting)

SANC: 3/8" - 1/2" - 3/4" - 1" - 1 1/4" - 1 1/2" - 2" (single acting normally closed)


SANO: 3/8" - 1/2" - 3/4" - 1" - 1 1/4" - 1 1/2" - 2" (single acting normally open)

Anodiserende behandlet udvendigt i aluminium

DOUBLE ACTING													
DN	G	AS/3/8"	A	S	C	F	E	Wrench	F ₁	Weight			
mm	Type	mm	mm	mm	mm	mm	mm	mm	kg	lb			
10	3/8"	AS5002	210	95	12	9	43	25	10	152			
15	1/2"	AS5002	270	108	12	9	43	32	20	1203			
20	3/4"	AS5002	270	108	12	9	43	32	20	1203			
25	1"	AS5002	270	108	12	9	43	32	20	1203			
32	1 1/4"	AS6013	280	213	12	10	50	32	100	1303			
40	1 1/2"	AS6013	270	208	12	10	50	32	100	1303			
50	2"	AS6013	317	273	16	10	50	40	180	1243			
65	2 1/2"	AS7014	340	288	18	11	50	50	350	4803			
80	3"	AS7014	357	307	18	11	50	50	350	4803			
100	4"	AS7014	417	367	18	11	50	50	350	4803			

SINGLE ACTING (NC-NO)													
DN	G	AS/3/8"	A	S	C	F	E	Wrench	F ₁	Weight			
mm	Type	mm	mm	mm	mm	mm	mm	mm	kg	lb			
10	3/8"	AS5002	210	95	12	9	43	25	10	152			
15	1/2"	AS5002	270	108	12	9	43	32	20	1203			
20	3/4"	AS5002	270	108	12	9	43	32	20	1203			
25	1"	AS5002	270	108	12	9	43	32	20	1203			
32	1 1/4"	AS6013	280	213	12	10	50	32	100	1303			
40	1 1/2"	AS6013	270	208	12	10	50	32	100	1303			
50	2"	AS6013	317	273	16	10	50	40	180	1243			
65	2 1/2"	AS7014	340	288	18	11	50	50	350	4803			
80	3"	AS7014	357	307	18	11	50	50	350	4803			
100	4"	AS7014	417	367	18	11	50	50	350	4803			

OVERALL DIMENSIONS




RATED PRESSURE "PN"									
G	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"
PN	64	64	64	40	40	40	25	25	25

DOUBLE ACTING													
DN	G	AS/3/8"	A	S	C	F	E	Wrench	F ₁	Weight			
mm	Type	mm	mm	mm	mm	mm	mm	mm	kg	lb			
10	3/8"	AS5002	210	95	12	9	43	25	10	152			
15	1/2"	AS5002	270	108	12	9	43	32	20	1203			
20	3/4"	AS5002	270	108	12	9	43	32	20	1203			
25	1"	AS5002	270	108	12	9	43	32	20	1203			
32	1 1/4"	AS6013	280	213	12	10	50	32	100	1303			
40	1 1/2"	AS6013	270	208	12	10	50	32	100	1303			
50	2"	AS6013	317	273	16	10	50	40	180	1243			
65	2 1/2"	AS7014	340	288	18	11	50	50	350	4803			
80	3"	AS7014	357	307	18	11	50	50	350	4803			
100	4"	AS7014	417	367	18	11	50	50	350	4803			

SINGLE ACTING (NC-NO)													
DN	G	AS/3/8"	A	S	C	F	E	Wrench	F ₁	Weight			
mm	Type	mm	mm	mm	mm	mm	mm	mm	kg	lb			
10	3/8"	AS5002	210	95	12	9	43	25	10	152			
15	1/2"	AS5002	270	108	12	9	43	32	20	1203			
20	3/4"	AS5002	270	108	12	9	43	32	20	1203			
25	1"	AS5002	270	108	12	9	43	32	20	1203			
32	1 1/4"	AS6013	280	213	12	10	50	32	100	1303			
40	1 1/2"	AS6013	270	208	12	10	50	32	100	1303			
50	2"	AS6013	317	273	16	10	50	40	180	1243			
65	2 1/2"	AS7014	340	288	18	11	50	50	350	4803			
80	3"	AS7014	357	307	18	11	50	50	350	4803			
100	4"	AS7014	417	367	18	11	50	50	350	4803			

OVERALL DIMENSIONS



RATED PRESSURE "PN"									
G	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"
PN	64	64	64	40	40	40	25	25	25