

METAL BELLOWS SHUT-OFF VENTIL

MBSOV-SERIEN Metal Bellows Shut-off Valve

- Tryk: PN 40
- CV= 1.4
- Temperaturområde: -20 til 70°C
- Vægt: 0.4 kg



D42528



D43129

PRODUKTBESKRIVELSE

Tescom Metal Bellows Shut-off-ventil

Til højren gasser i laboratorieapplikationer.

Applikationer

- Ren gasapplikationer
- Højflow-systemer
- Rensningsproces
- Anvendes i hovedlinjer



Fordele

- Fuldt metal design forhindrer gasforurening
- Rustfrit stål bellows og poppet
- Farvekodet gas på håndhjulet for let identifikation
- Oxygenrenset
- Fri for olie og fedt

Example for selecting a part number:

D43129	AR	11
BASIC SERIES	GAS TYPE LABELING ON HANDWHEEL AND CAPS	CONNECTIONS
D42528 D43129	According to DIN EN 13792* AD - Oxygen and other gases *Color handwheel and cap = gas label according to DIN EN 13792 *State type of gas when ordering. Standard color for handwheels is grey. Please refer to additional colors if needed.	00 - Female G 1/8 Compression fittings in Brass/Stainless Steel are available, please refer to datasheet "Fittings"

Note: When selecting valves, the compatibility of the materials with the process gas must be verified.




Example for selecting a part number:

D43129	AR	11
BASIC SERIES	GAS TYPE LABELING ON HANDWHEEL AND CAPS	CONNECTIONS
D42528 D43129	According to DIN EN 13792* AD - Oxygen and other gases *Color handwheel and cap = gas label according to DIN EN 13792 *State type of gas when ordering. Standard color for handwheels is grey. Please refer to additional colors if needed.	00 - Female G 1/8 Compression fittings in Brass/Stainless Steel are available, please refer to datasheet "Fittings"

Note: When selecting valves, the compatibility of the materials with the process gas must be verified.

D42528



D43129

