

EFFEPI MESSING 3-VEJS
KUGLEVENTILER \\"L\\" BORRET KUGLE
TYPE F3L


EFFF3L15SA

Kemi 3-vejs kugleventil \\"L\\" borret DN15 Single acting

- Materiale: Messing OT58 nikkel belagt
- Medier: Gas, Olie, Væske
- Størrelser: DN15 - DN50
- Fås med pneumatisk aktuator
- Temperaturområde -15°C - +100°C



PRODUKTBESKRIVELSE




RATED PRESSURE "PN"							
G	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	
PN	40	40	25	16	16	16	

DOUBLE ACTING											
DN	G	ACTUATOR	A	B	C	D	E	F	Weight	Weight	Weight
mm		Type	mm	mm	mm	mm	mm	mm	kg	kg	kg
15	1/2"	SEA302	275	226	80	10	22	43	27	4	5145
20	3/4"	SEA302	275	226	80	10	22	43	27	4	5145
25	1"	SEA302	275	226	80	10	22	43	27	4	5145
32	1 1/4"	SEA302	275	226	80	10	22	43	27	4	5145
40	1 1/2"	SEA302	275	226	80	10	22	43	27	4	5145
50	2"	SEA302	275	226	80	10	22	43	27	4	5145

SINGLE ACTING											
DN	G	ACTUATOR	A	B	C	D	E	F	Weight	Weight	Weight
mm		Type	mm	mm	mm	mm	mm	mm	kg	kg	kg
15	1/2"	SEA302	275	226	80	10	22	43	27	4	5145
20	3/4"	SEA302	275	226	80	10	22	43	27	4	5145
25	1"	SEA302	275	226	80	10	22	43	27	4	5145
32	1 1/4"	SEA302	275	226	80	10	22	43	27	4	5145
40	1 1/2"	SEA302	275	226	80	10	22	43	27	4	5145
50	2"	SEA302	275	226	80	10	22	43	27	4	5145

OVERALL DIMENSIONS											
DN	G	ACTUATOR	A	B	C	D	E	F	Weight	Weight	Weight
mm		Type	mm	mm	mm	mm	mm	mm	kg	kg	kg
15	1/2"	SEA302	275	226	80	10	22	43	27	4	5145
20	3/4"	SEA302	275	226	80	10	22	43	27	4	5145
25	1"	SEA302	275	226	80	10	22	43	27	4	5145
32	1 1/4"	SEA302	275	226	80	10	22	43	27	4	5145
40	1 1/2"	SEA302	275	226	80	10	22	43	27	4	5145
50	2"	SEA302	275	226	80	10	22	43	27	4	5145



RATED PRESSURE "PN"							
G	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	
PN	40	40	25	16	16	16	

OVERALL DIMENSIONS

DOUBLE ACTING

IN	G	ACTUATOR	A	B	C	D	E	F	WEIGHT	Wt	Wt
1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"
1"	1"	1"	1"	1"	1"	1"	1"	1"	1"	1"	1"
1 1/4"	1 1/4"	1 1/4"	1 1/4"	1 1/4"	1 1/4"	1 1/4"	1 1/4"	1 1/4"	1 1/4"	1 1/4"	1 1/4"
1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"
2"	2"	2"	2"	2"	2"	2"	2"	2"	2"	2"	2"

SINGLE ACTING

IN	G	ACTUATOR	A	B	C	D	E	F	WEIGHT	Wt	Wt
1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"
1"	1"	1"	1"	1"	1"	1"	1"	1"	1"	1"	1"
1 1/4"	1 1/4"	1 1/4"	1 1/4"	1 1/4"	1 1/4"	1 1/4"	1 1/4"	1 1/4"	1 1/4"	1 1/4"	1 1/4"
1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"
2"	2"	2"	2"	2"	2"	2"	2"	2"	2"	2"	2"