

EFFEPI RUSTFRI STÅL KUGLEVENTILER TYPE \"AL\" AISI 304

EFFAL10DA

Kemi rustfri stål kugleventil DN10 double acting
AISI304

- Materiale: Rustfri stål AISI 304
- Medier: Gas, Olie, Væske
- Størrelser: DN10 - DN100 (DA) DN10 - DN50 (SA)
- Fås med pneumatisk aktuator
- Temperaturområde: -15°C - +100°C



PRODUKTBESKRIVELSE

Rustfri stål kugleventil med roterende pneumatisk aktuator.

Ventilkrop: Rustfri stål AISI304

Kugle: Rustfri stål AISI304

Pakning: Virgin PTFE

Temperaturområder:

-15°C - +100°C

Max temperatur for special brug (med fuldt åben ventil):

+100°C brændstofs olier, mineral olier og mageriner

+90°C hav og drikkevand

+60°C trichlorethylen, butan, methan, propan, carbon dioxide

+40°C Alkohol, benzin, lette gasser, naturlige gasser, lime vand, sodavand.

Aktuator tryk:

Double acting fra 3 - 8 bar

Single acting fra 6 - 8 bar

Tilslutninger med GAS ISO228 hun-hun fittings.

Kan leveres med NPT eller DIN tilslutning

GAS tilslutning 1/8"

DA: 3/8" - 1/2" - 3/4" - 1" - 1 1/4" - 1 1/2" - 2" - 2 1/2" - 3" - 4" (double acting)

SANC: 3/8" - 1/2" - 3/4" - 1" - 1 1/4" - 1 1/2" - 2" (single acting normally closed)


SANO: 3/8" - 1/2" - 3/4" - 1" - 1 1/4" - 1 1/2" - 2" (single acting normally open)

Anodiserende behandlet udvendigt i aluminium

DOUBLE ACTING													
DN	G	AS/3/8"	A	B	C	D	E	stroke	F ₁	weight			
mm	Type	mm	mm	mm	mm	mm	mm	mm	kg	lb			
10	3/8"	AS5002	210	95	12	9	43	25	10	152			
15	1/2"	AS5002	270	108	12	9	43	32	20	1203			
20	3/4"	AS5002	270	125	12	9	43	32	20	1203			
25	1"	AS5002	270	125	12	9	43	32	20	1203			
32	1 1/4"	AS6003	280	125	12	9	43	32	20	1203			
40	1 1/2"	AS6003	270	125	12	9	43	32	20	1203			
50	2"	AS6003	317	125	12	9	43	32	20	1203			
65	2 1/2"	AS7004	340	125	12	9	43	32	20	1203			
80	3"	AS7004	340	125	12	9	43	32	20	1203			
100	4"	AS7004	340	125	12	9	43	32	20	1203			

SINGLE ACTING (NC-NO)													
DN	G	AS/3/8"	A	B	C	D	E	stroke	F ₁	weight			
mm	Type	mm	mm	mm	mm	mm	mm	mm	kg	lb			
10	3/8"	AS5002	210	95	12	9	43	25	10	152			
15	1/2"	AS5002	270	108	12	9	43	32	20	1203			
20	3/4"	AS6003	280	125	12	9	43	32	20	1203			
25	1"	AS6003	270	125	12	9	43	32	20	1203			
32	1 1/4"	AS6003	280	125	12	9	43	32	20	1203			
40	1 1/2"	AS6003	270	125	12	9	43	32	20	1203			
50	2"	AS6003	317	125	12	9	43	32	20	1203			
65	2 1/2"	AS7004	340	125	12	9	43	32	20	1203			
80	3"	AS7004	340	125	12	9	43	32	20	1203			
100	4"	AS7004	340	125	12	9	43	32	20	1203			

OVERALL DIMENSIONS




RATED PRESSURE "PN"									
G	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"
PN	64	64	64	40	40	40	25	25	25

DOUBLE ACTING													
DN	G	AS/3/8"	A	B	C	D	E	stroke	F ₁	weight			
mm	Type	mm	mm	mm	mm	mm	mm	mm	kg	lb			
10	3/8"	AS5002	210	95	12	9	43	25	10	152			
15	1/2"	AS5002	270	108	12	9	43	32	20	1203			
20	3/4"	AS5002	270	125	12	9	43	32	20	1203			
25	1"	AS5002	270	125	12	9	43	32	20	1203			
32	1 1/4"	AS6003	280	125	12	9	43	32	20	1203			
40	1 1/2"	AS6003	270	125	12	9	43	32	20	1203			
50	2"	AS6003	317	125	12	9	43	32	20	1203			
65	2 1/2"	AS7004	340	125	12	9	43	32	20	1203			
80	3"	AS7004	340	125	12	9	43	32	20	1203			
100	4"	AS7004	340	125	12	9	43	32	20	1203			

SINGLE ACTING (NC-NO)													
DN	G	AS/3/8"	A	B	C	D	E	stroke	F ₁	weight			
mm	Type	mm	mm	mm	mm	mm	mm	mm	kg	lb			
10	3/8"	AS5002	210	95	12	9	43	25	10	152			
15	1/2"	AS5002	270	108	12	9	43	32	20	1203			
20	3/4"	AS6003	280	125	12	9	43	32	20	1203			
25	1"	AS6003	270	125	12	9	43	32	20	1203			
32	1 1/4"	AS6003	280	125	12	9	43	32	20	1203			
40	1 1/2"	AS6003	270	125	12	9	43	32	20	1203			
50	2"	AS6003	317	125	12	9	43	32	20	1203			
65	2 1/2"	AS7004	340	125	12	9	43	32	20	1203			
80	3"	AS7004	340	125	12	9	43	32	20	1203			
100	4"	AS7004	340	125	12	9	43	32	20	1203			

OVERALL DIMENSIONS



RATED PRESSURE "PN"									
G	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"
PN	64	64	64	40	40	40	25	25	25