

EFFEPI RUSTFRI STÅL KUGLEVENTIL TYPE \"AL1\" AISI 316

EFFAL110DA

Kemi rustfri stål kugleventil DN10 double acting
AISI316

- Materiale: Rustfri stål AISI 316
- Medier: Gas, Olie, Væske
- Størrelser: DN10 - DN100 (DA) DN10 - DN50 (SA)
- Fås med pneumatisk aktuator
- Temperaturområde: -15°C - +100°C



PRODUKTBESKRIVELSE

Rustfri stål kugleventil med roterende pneumatisk aktuator.

Ventilkrop: Rustfri stål AISI316

Kugle: Rustfri stål AISI316

Pakning: Virgin PTFE

Temperaturområder:

-15°C - +100°C

Max temperatur for special brug (med fuldt åben ventil):

+100°C brændstofs olier, mineral olier og mageriner

+90°C hav og drikkevand

+60°C trichlorethylen, butan, methan, propan, carbon dioxide

+40°C Alkohol, benzin, lette gasser, naturlige gasser, lime vand, sodavand.

Aktuator tryk:

Double acting fra 3 - 8 bar

Single acting fra 6 - 8 bar

Tilslutninger med GAS ISO228 hun-hun fittings.

Kan leveres med NPT eller DIN tilslutning

GAS tilslutning 1/8"

DA: 3/8" - 1/2" - 3/4" - 1" - 1 1/4" - 1 1/2" - 2" - 2 1/2" - 3" - 4" (double acting)

SANC: 3/8" - 1/2" - 3/4" - 1" - 1 1/4" - 1 1/2" - 2" (single acting normally closed)


SANO: 3/8" - 1/2" - 3/4" - 1" - 1 1/4" - 1 1/2" - 2" (single acting normally open)

Anodiserende behandlet udvendigt i aluminium

DOUBLE ACTING													
DN	G	AS/3/8"	A	B	C	D	E	stroke	F ₁	weight			
mm	Type	mm	mm	mm	mm	mm	mm	mm	kg	lb			
10	3/8"	AS5002	210	95	12	6	43	25	10	152			
15	1/2"	AS5002	270	108	12	7	45	32	20	1203			
20	3/4"	AS5002	270	125	12	7	47	38	30	1503			
25	1"	AS5002	270	125	12	7	47	48	50	2103			
32	1 1/4"	AS6003	280	210	12	10	50	52	100	1303			
40	1 1/2"	AS6003	270	205	12	10	50	55	110	1403			
50	2"	AS6003	317	273	16	10	50	60	180	2503			
65	2 1/2"	AS7004	340	288	18	15	110	100	350	4803			
80	3"	AS7005	437	357	18	15	115	110	380	5203			
100	4"	AS7005	437	357	18	15	115	125	400	5503			

SINGLE ACTING (NC-NO)													
DN	G	AS/3/8"	A	B	C	D	E	stroke	F ₁	weight			
mm	Type	mm	mm	mm	mm	mm	mm	mm	kg	lb			
10	3/8"	AS5002	210	95	12	6	43	25	10	152			
15	1/2"	AS5002	270	108	12	7	45	32	20	1203			
20	3/4"	AS5002	270	125	12	7	47	38	30	1503			
25	1"	AS5002	270	125	12	7	47	48	50	2103			
32	1 1/4"	AS6003	280	210	12	10	50	52	100	1303			
40	1 1/2"	AS6003	270	205	12	10	50	55	110	1403			
50	2"	AS6003	317	273	16	10	50	60	180	2503			
65	2 1/2"	AS7004	340	288	18	15	110	100	350	4803			
80	3"	AS7005	437	357	18	15	115	110	380	5203			
100	4"	AS7005	437	357	18	15	115	125	400	5503			

OVERALL DIMENSIONS




RATED PRESSURE "PN"									
G	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"
PN	64	64	64	40	40	40	25	25	25

DOUBLE ACTING													
DN	G	AS/3/8"	A	B	C	D	E	stroke	F ₁	weight			
mm	Type	mm	mm	mm	mm	mm	mm	mm	kg	lb			
10	3/8"	AS5002	210	95	12	6	43	25	10	152			
15	1/2"	AS5002	270	108	12	7	45	32	20	1203			
20	3/4"	AS5002	270	125	12	7	47	38	30	1503			
25	1"	AS5002	270	125	12	7	47	48	50	2103			
32	1 1/4"	AS6003	280	210	12	10	50	52	100	1303			
40	1 1/2"	AS6003	270	205	12	10	50	55	110	1403			
50	2"	AS6003	317	273	16	10	50	60	180	2503			
65	2 1/2"	AS7004	340	288	18	15	110	100	350	4803			
80	3"	AS7005	437	357	18	15	115	110	380	5203			
100	4"	AS7005	437	357	18	15	115	125	400	5503			

SINGLE ACTING (NC-NO)													
DN	G	AS/3/8"	A	B	C	D	E	stroke	F ₁	weight			
mm	Type	mm	mm	mm	mm	mm	mm	mm	kg	lb			
10	3/8"	AS5002	210	95	12	6	43	25	10	152			
15	1/2"	AS5002	270	108	12	7	45	32	20	1203			
20	3/4"	AS5002	270	125	12	7	47	38	30	1503			
25	1"	AS5002	270	125	12	7	47	48	50	2103			
32	1 1/4"	AS6003	280	210	12	10	50	52	100	1303			
40	1 1/2"	AS6003	270	205	12	10	50	55	110	1403			
50	2"	AS6003	317	273	16	10	50	60	180	2503			
65	2 1/2"	AS7004	340	288	18	15	110	100	350	4803			
80	3"	AS7005	437	357	18	15	115	110	380	5203			
100	4"	AS7005	437	357	18	15	115	125	400	5503			

OVERALL DIMENSIONS



RATED PRESSURE "PN"									
G	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"
PN	64	64	64	40	40	40	25	25	25