

# V-PAD TIL MÅLING AF UDETEMPERATUR

Serie TC59-V

TC59-V  
V-PAD

- Måleområde fra 0 op til 1260 °C
- Type K, J, N eller E
- Modstandsdygtig overfor mekanisk belastning
- Materiale i eksempelvis rustfrit stål, Hastelloy, Pyrosil D eller Haynes HR
- Option: ATEX-udførelse




## PRODUKTBESKRIVELSE

## SPECIFIKATIONER


Materiale mediebærte del	Hastelloy, Rustfrit stål
Temperaturområde fra	0 °C
Temperaturområde til	1260 °C

Fixed connection (compression fitting) to the furnace




- Cable length 150 mm, other lengths on request
- Compensating cable type depending on the sensor type, PTFE-insulated
- The sealing from the process is performed by the compression fitting, it can be supplied in most common thread sizes.
- A connection head can be mounted directly to the neck or remotely.

Sliding connection (piston/spring) to the furnace



Fixed connection (compression fitting) to the furnace



- Cable length 150 mm, other lengths on request
- Compensating cable type depending on the sensor type, PTFE-insulated
- The sealing from the process is performed by the compression fitting, it can be supplied in most common thread sizes.
- A connection head can be mounted directly to the neck or remotely.

Sliding connection (piston/spring) to the furnace

