



JUSTERBAR BAJONETFØLER TIL PLASTINDUSTRIEN

Serie TC47-AB

TC47-AB
Justerbar bajonetteføler

- Måleområde fra -40 op til 750°C
- Type J, L, K eller T (andre efter behov)
- Design med fjeder eller forstærkning
- Føleren kan justeres til egnet længde ved installation
- Meget let at skifte



PRODUKTBESKRIVELSE

SPECIFIKATIONER

Temperaturområde fra	-40 °C
Temperaturområde til	750 °C

<p>Adjustable bayonet</p> <ul style="list-style-type: none"> ■ Spring up to 200 mm or 8" of adjustability ■ Armour full lead length of adjustability <p>Junction</p> <ul style="list-style-type: none"> ■ Grounded (unisolated) ■ Ungrounded (isolated) <p>Tip diameter (Ø)</p> <ul style="list-style-type: none"> ■ 3/16" ■ 1/4" ■ 3/8" ■ 4 mm ■ 6 mm ■ 8 mm ■ 10 mm ■ Others on request <p>Probe length</p> <ul style="list-style-type: none"> ■ Standard ■ Others on request <p>Bayonet cap</p> <table border="0"> <tr> <td>Single slot</td> <td>11.4 mm (7/16")</td> <td>11 mm O.D.</td> </tr> <tr> <td>Double slot</td> <td>11.4 mm (7/16")</td> <td>11 mm O.D.</td> </tr> <tr> <td>Double slot</td> <td>12.2 mm (3/16")</td> <td>12 mm O.D.</td> </tr> <tr> <td>Double slot</td> <td>14.2 mm (9/16")</td> <td>12 mm O.D.</td> </tr> <tr> <td>Double slot</td> <td>15.2 mm (19/32")</td> <td>15 mm O.D.</td> </tr> </table> <p>■ Others on request</p> <p>Lead length</p> <ul style="list-style-type: none"> ■ 500 mm ■ 1000 mm ■ 1500 mm ■ 2000 mm ■ 2500 mm ■ Others on request 	Single slot	11.4 mm (7/16")	11 mm O.D.	Double slot	11.4 mm (7/16")	11 mm O.D.	Double slot	12.2 mm (3/16")	12 mm O.D.	Double slot	14.2 mm (9/16")	12 mm O.D.	Double slot	15.2 mm (19/32")	15 mm O.D.	<p>Lead wire</p> <ul style="list-style-type: none"> ■ Fibreglass / Fibreglass ■ PTFE / PTFE ■ PVC / PVC ■ Kapton / Kapton ■ Others on request <p>Lead wire covering</p> <ul style="list-style-type: none"> ■ None ■ Stainless steel overbraid (no tracer) ■ Stainless steel overbraid (with tracer) ■ Tin copper overbraid ■ Interlocking flexible armour <p>Termination at lead end</p> <ul style="list-style-type: none"> ■ Bare ends ■ Standard thermo plug 2-pin (male) ■ Miniature thermo plug 2-pin (male) ■ Standard plug with cable clamp (male) ■ Miniature plug with cable clamp (male) ■ Lemosa plug size 1S (male) ■ Lemosa plug size 2S (male) ■ Screw-in plug, Binder (male) ■ Others on request <p>Calibration type</p> <table border="0"> <tr> <td>J</td> <td>ANSI MC96.1</td> <td>red ⊕</td> <td>white ⊖</td> </tr> <tr> <td>K</td> <td>ANSI MC96.1</td> <td>red ⊕</td> <td>yellow ⊖</td> </tr> <tr> <td>T</td> <td>ANSI MC96.1</td> <td>red ⊕</td> <td>blue ⊖</td> </tr> <tr> <td>J</td> <td>IEC 584-3</td> <td>white ⊕</td> <td>black ⊖</td> </tr> <tr> <td>K</td> <td>IEC 584-3</td> <td>white ⊕</td> <td>green ⊖</td> </tr> <tr> <td>T</td> <td>IEC 584-3</td> <td>white ⊕</td> <td>brown ⊖</td> </tr> <tr> <td>J</td> <td>DIN 43714</td> <td>blue ⊕</td> <td>red ⊖</td> </tr> <tr> <td>K</td> <td>DIN 43714</td> <td>green ⊕</td> <td>red ⊖</td> </tr> <tr> <td>T</td> <td>DIN 43714</td> <td>brown ⊕</td> <td>red ⊖</td> </tr> </table> <p>■ Others on request</p>	J	ANSI MC96.1	red ⊕	white ⊖	K	ANSI MC96.1	red ⊕	yellow ⊖	T	ANSI MC96.1	red ⊕	blue ⊖	J	IEC 584-3	white ⊕	black ⊖	K	IEC 584-3	white ⊕	green ⊖	T	IEC 584-3	white ⊕	brown ⊖	J	DIN 43714	blue ⊕	red ⊖	K	DIN 43714	green ⊕	red ⊖	T	DIN 43714	brown ⊕	red ⊖	<p>Adjustable bayonet</p> <ul style="list-style-type: none"> ■ Spring up to 200 mm or 8" of adjustability ■ Armour full lead length of adjustability <p>Junction</p> <ul style="list-style-type: none"> ■ Grounded (unisolated) ■ Ungrounded (isolated) <p>Tip diameter (Ø)</p> <ul style="list-style-type: none"> ■ 3/16" ■ 1/4" ■ 3/8" ■ 4 mm ■ 6 mm ■ 8 mm ■ 10 mm ■ Others on request <p>Probe length</p> <ul style="list-style-type: none"> ■ Standard ■ Others on request <p>Bayonet cap</p> <table border="0"> <tr> <td>Single slot</td> <td>11.4 mm (7/16")</td> <td>11 mm O.D.</td> </tr> <tr> <td>Double slot</td> <td>11.4 mm (7/16")</td> <td>11 mm O.D.</td> </tr> <tr> <td>Double slot</td> <td>12.2 mm (3/16")</td> <td>12 mm O.D.</td> </tr> <tr> <td>Double slot</td> <td>14.2 mm (9/16")</td> <td>12 mm O.D.</td> </tr> <tr> <td>Double slot</td> <td>15.2 mm (19/32")</td> <td>15 mm O.D.</td> </tr> </table> <p>■ Others on request</p> <p>Lead length</p> <ul style="list-style-type: none"> ■ 500 mm ■ 1000 mm ■ 1500 mm ■ 2000 mm ■ 2500 mm ■ Others on request 	Single slot	11.4 mm (7/16")	11 mm O.D.	Double slot	11.4 mm (7/16")	11 mm O.D.	Double slot	12.2 mm (3/16")	12 mm O.D.	Double slot	14.2 mm (9/16")	12 mm O.D.	Double slot	15.2 mm (19/32")	15 mm O.D.	<p>Lead wire</p> <ul style="list-style-type: none"> ■ Fibreglass / Fibreglass ■ PTFE / PTFE ■ PVC / PVC ■ Kapton / Kapton ■ Others on request <p>Lead wire covering</p> <ul style="list-style-type: none"> ■ None ■ Stainless steel overbraid (no tracer) ■ Stainless steel overbraid (with tracer) ■ Tin copper overbraid ■ Interlocking flexible armour <p>Termination at lead end</p> <ul style="list-style-type: none"> ■ Bare ends ■ Standard thermo plug 2-pin (male) ■ Miniature thermo plug 2-pin (male) ■ Standard plug with cable clamp (male) ■ Miniature plug with cable clamp (male) ■ Lemosa plug size 1S (male) ■ Lemosa plug size 2S (male) ■ Screw-in plug, Binder (male) ■ Others on request <p>Calibration type</p> <table border="0"> <tr> <td>J</td> <td>ANSI MC96.1</td> <td>red ⊕</td> <td>white ⊖</td> </tr> <tr> <td>K</td> <td>ANSI MC96.1</td> <td>red ⊕</td> <td>yellow ⊖</td> </tr> <tr> <td>T</td> <td>ANSI MC96.1</td> <td>red ⊕</td> <td>blue ⊖</td> </tr> <tr> <td>J</td> <td>IEC 584-3</td> <td>white ⊕</td> <td>black ⊖</td> </tr> <tr> <td>K</td> <td>IEC 584-3</td> <td>white ⊕</td> <td>green ⊖</td> </tr> <tr> <td>T</td> <td>IEC 584-3</td> <td>white ⊕</td> <td>brown ⊖</td> </tr> <tr> <td>J</td> <td>DIN 43714</td> <td>blue ⊕</td> <td>red ⊖</td> </tr> <tr> <td>K</td> <td>DIN 43714</td> <td>green ⊕</td> <td>red ⊖</td> </tr> <tr> <td>T</td> <td>DIN 43714</td> <td>brown ⊕</td> <td>red ⊖</td> </tr> </table> <p>■ Others on request</p>	J	ANSI MC96.1	red ⊕	white ⊖	K	ANSI MC96.1	red ⊕	yellow ⊖	T	ANSI MC96.1	red ⊕	blue ⊖	J	IEC 584-3	white ⊕	black ⊖	K	IEC 584-3	white ⊕	green ⊖	T	IEC 584-3	white ⊕	brown ⊖	J	DIN 43714	blue ⊕	red ⊖	K	DIN 43714	green ⊕	red ⊖	T	DIN 43714	brown ⊕	red ⊖
Single slot	11.4 mm (7/16")	11 mm O.D.																																																																																																							
Double slot	11.4 mm (7/16")	11 mm O.D.																																																																																																							
Double slot	12.2 mm (3/16")	12 mm O.D.																																																																																																							
Double slot	14.2 mm (9/16")	12 mm O.D.																																																																																																							
Double slot	15.2 mm (19/32")	15 mm O.D.																																																																																																							
J	ANSI MC96.1	red ⊕	white ⊖																																																																																																						
K	ANSI MC96.1	red ⊕	yellow ⊖																																																																																																						
T	ANSI MC96.1	red ⊕	blue ⊖																																																																																																						
J	IEC 584-3	white ⊕	black ⊖																																																																																																						
K	IEC 584-3	white ⊕	green ⊖																																																																																																						
T	IEC 584-3	white ⊕	brown ⊖																																																																																																						
J	DIN 43714	blue ⊕	red ⊖																																																																																																						
K	DIN 43714	green ⊕	red ⊖																																																																																																						
T	DIN 43714	brown ⊕	red ⊖																																																																																																						
Single slot	11.4 mm (7/16")	11 mm O.D.																																																																																																							
Double slot	11.4 mm (7/16")	11 mm O.D.																																																																																																							
Double slot	12.2 mm (3/16")	12 mm O.D.																																																																																																							
Double slot	14.2 mm (9/16")	12 mm O.D.																																																																																																							
Double slot	15.2 mm (19/32")	15 mm O.D.																																																																																																							
J	ANSI MC96.1	red ⊕	white ⊖																																																																																																						
K	ANSI MC96.1	red ⊕	yellow ⊖																																																																																																						
T	ANSI MC96.1	red ⊕	blue ⊖																																																																																																						
J	IEC 584-3	white ⊕	black ⊖																																																																																																						
K	IEC 584-3	white ⊕	green ⊖																																																																																																						
T	IEC 584-3	white ⊕	brown ⊖																																																																																																						
J	DIN 43714	blue ⊕	red ⊖																																																																																																						
K	DIN 43714	green ⊕	red ⊖																																																																																																						
T	DIN 43714	brown ⊕	red ⊖																																																																																																						