



FØLER MED SKÆRERINGSFORSKRUNING TIL PLASTINDUSTRIEN

Serie TC47-AC

TC47-AC

Føler med skæreringsforskruning

- Måleområde fra -40 op til 750°C
- Type J, L K eller T (andre efter behov)
- Rustfrit stålkappe eller legeringer mod oxidation ved høj temperatur
- Kun rør og tråd-design
- Valgfri størrelse af gevind



PRODUKTBESKRIVELSE

SPECIFIKATIONER

Temperaturområde fra

-40 °C

Temperaturområde til

750 °C

Adjustable compression version ■ Straight ■ 45° bend ■ 90° bend	Lead wire ■ Fibreglass / fibreglass ■ PTFE / PTFE ■ PVC / PVC ■ Kapton / Kapton ■ Others on request	Adjustable compression version ■ Straight ■ 45° bend ■ 90° bend	Lead wire ■ Fibreglass / fibreglass ■ PTFE / PTFE ■ PVC / PVC ■ Kapton / Kapton ■ Others on request
Junction ■ Grounded (unisolated) ■ Ungrounded (isolated)	Lead wire covering ■ None ■ Stainless steel overbraid (no tracer) ■ Stainless steel overbraid (with tracer) ■ Tin copper overbraid ■ Interlocking flexible armour	Junction ■ Grounded (unisolated) ■ Ungrounded (isolated)	Lead wire covering ■ None ■ Stainless steel overbraid (no tracer) ■ Stainless steel overbraid (with tracer) ■ Tin copper overbraid ■ Interlocking flexible armour
Probe diameter ■ 3/16" ■ 1/4" ■ 3/8" ■ 4 mm ■ 6 mm ■ 8 mm ■ Others on request	Termination at lead end ■ Bare ends ■ Standard thermo plug 2-pin (male) ■ Miniature thermo plug 2-pin (male)	Probe diameter ■ 3/16" ■ 1/4" ■ 3/8" ■ 4 mm ■ 6 mm ■ 8 mm ■ Others on request	Termination at lead end ■ Bare ends ■ Standard thermo plug 2-pin (male) ■ Miniature thermo plug 2-pin (male)
Probe length ■ Standard: 100 mm (4") ■ Others on request	Compression fitting material ■ Brass ■ Stainless steel ■ None	Probe length ■ Standard: 100 mm (4") ■ Others on request	Compression fitting material ■ Brass ■ Stainless steel ■ None
Thread size ■ Thread size on request	Calibration type ■ J: ANSI MC96.1 red Ø white Ø ■ K: ANSI MC96.1 red Ø yellow Ø ■ T: ANSI MC96.1 red Ø blue Ø ■ J: IEC 584-3 white Ø black Ø ■ K: IEC 584-3 white Ø green Ø ■ T: IEC 584-3 white Ø brown Ø ■ J: DIN 43714 blue Ø red Ø ■ K: DIN 43714 green Ø red Ø ■ T: DIN 43714 brown Ø red Ø ■ Others on request	Thread size ■ Thread size on request	Calibration type ■ J: ANSI MC96.1 red Ø white Ø ■ K: ANSI MC96.1 red Ø yellow Ø ■ T: ANSI MC96.1 red Ø blue Ø ■ J: IEC 584-3 white Ø black Ø ■ K: IEC 584-3 white Ø green Ø ■ T: IEC 584-3 white Ø brown Ø ■ J: DIN 43714 blue Ø red Ø ■ K: DIN 43714 green Ø red Ø ■ T: DIN 43714 brown Ø red Ø ■ Others on request
Lead length ■ 500 mm ■ 1000 mm ■ 1500 mm ■ 2000 mm ■ 2500 mm ■ Others on request		Lead length ■ 500 mm ■ 1000 mm ■ 1500 mm ■ 2000 mm ■ 2500 mm ■ Others on request	