



FØLER MED RINGFÆSTE TIL PLASTINDUSTRIEN

Serie TC47-RL

TC47-RL
Termoelement med ringfæste

- Måleområde fra -40 op til 750 °C
- Type J, L, K, eller T (andre efter behov)
- Ringøje af rustfrit stål
- Forlængerkabel i eksempelvis PTFE, fiberglas eller PVC
- Meget let at installere og skifte ud



PRODUKTBESKRIVELSE

SPECIFIKATIONER

Temperaturområde fra	-40 °C
Temperaturområde til	750 °C

 Ring lug material ■ Stainless steel ■ Nickel clad copper ■ Others on request Junction ■ Grounded (unisolated) ■ Ungrounded (isolated) Ring Ø size ■ 4.2 mm ■ 5.2 mm ■ 6.2 mm ■ Others on request Lead length ■ 500 mm ■ 1000 mm ■ 1500 mm ■ 2000 mm ■ 2500 mm ■ Others on request Lead wire ■ Fiberglass / fiberglass ■ PTFE / PTFE ■ PVC / PVC ■ Kapton / Kapton ■ Others on request Lead wire covering ■ None ■ Stainless steel overbraid (no tracer) ■ Stainless steel overbraid (with tracer) ■ Tin copper overbraid	 Termination at lead end ■ Bare ends ■ Standard thermo plug 2-pin (male) ■ Miniature thermo plug 2-pin (male) ■ Standard plug with cable clamp (male) ■ Miniature plug with cable clamp (male) ■ Lemosa plug size 15 (male) ■ Lemosa plug size 25 (male) ■ Screw-in plug, Binder (male) ■ Others on request Calibration type ■ J ANSI MC96.1 red Ø white Ø ■ K ANSI MC96.1 red Ø yellow Ø ■ T ANSI MC96.1 red Ø blue Ø ■ J IEC 584-3 white Ø black Ø ■ K IEC 584-3 white Ø green Ø ■ T IEC 584-3 white Ø brown Ø ■ J DIN 43714 blue Ø red Ø ■ K DIN 43714 green Ø red Ø ■ T DIN 43714 brown Ø red Ø ■ Others on request	 Ring lug material ■ Stainless steel ■ Nickel clad copper ■ Others on request Junction ■ Grounded (unisolated) ■ Ungrounded (isolated) Ring Ø size ■ 4.2 mm ■ 5.2 mm ■ 6.2 mm ■ Others on request Lead length ■ 500 mm ■ 1000 mm ■ 1500 mm ■ 2000 mm ■ 2500 mm ■ Others on request Lead wire ■ Fiberglass / fiberglass ■ PTFE / PTFE ■ PVC / PVC ■ Kapton / Kapton ■ Others on request Lead wire covering ■ None ■ Stainless steel overbraid (no tracer) ■ Stainless steel overbraid (with tracer) ■ Tin copper overbraid	 Termination at lead end ■ Bare ends ■ Standard thermo plug 2-pin (male) ■ Miniature thermo plug 2-pin (male) ■ Standard plug with cable clamp (male) ■ Miniature plug with cable clamp (male) ■ Lemosa plug size 15 (male) ■ Lemosa plug size 25 (male) ■ Screw-in plug, Binder (male) ■ Others on request Calibration type ■ J ANSI MC96.1 red Ø white Ø ■ K ANSI MC96.1 red Ø yellow Ø ■ T ANSI MC96.1 red Ø blue Ø ■ J IEC 584-3 white Ø black Ø ■ K IEC 584-3 white Ø green Ø ■ T IEC 584-3 white Ø brown Ø ■ J DIN 43714 blue Ø red Ø ■ K DIN 43714 green Ø red Ø ■ T DIN 43714 brown Ø red Ø ■ Others on request
--	--	--	---