

EFFEPI 3-VEJS LAVTRYKS KUGLEVENTILER TYPE F3D

EFFF3D15SA

Kemi messing 3-vejs kugleventil DN15 single acting

- Materiale: Messing OT58 nikkel belagt
- Medier: Gas, Olie, Væske
- Størrelser: DN15 - DN50
- Fås med pneumatisk aktuator
- Temperaturområde: -15°C - +100°C



PRODUKTBESKRIVELSE

Messing 3-vejs kugleventil med roterende pneumatisk aktuator.

Ventilkrop: Messing OT58 nikkel belagt.

Kugle: Messing OT58 heavy duty forkromet.

Pakning: Virgin PTFE

Funktioner: 3-vejs (2 positioner)

Temperaturområder:

-15°C - +100°C

Max temperatur for special brug (ventil fuldt open):

+100°C brændstofs olier, mineral olier og mageriner

+90°C hav og drikkevand

+60°C trichlorethylen, butan, methan, propan, carbon dioxide

+40°C Alkohol, benzin, lette gasser, natur gasser, lime vand, sodavand.

Aktuator tryk:

Double acting fra 3 - 8 bar

Single acting fra 5 - 8 bar

Tilslutninger med GAS ISO228 hun-hun fittings.

Kan leveres med NPT-forbindelser



GAS tilslutning 1/8"

DA: 1/2" - 3/4" - 1" - 1 1/4" - 1 1/2" - 2" (double acting)

SA: 1/2" - 3/4" - 1" - 1 1/4" - 1 1/2" - 2" (single acting)



Anodiserende behandlet udvendigt i aluminium

DOUBLE ACTING											
DN	G	AS/4100	A	B	C	D	E	F	Intersect	R _x	Weight
mm		Type	mm	mm	mm	mm	mm	mm	mm	mm	lb
15	1/2"	SE1502	275	107	43	15	15	13	23	5	1150
20	3/4"	SE1503	282	220	77	23	17	45	33	5	1500
25	1"	SE1504	288	229	89	25	17	73	40	10	1800
32	1 1/4"	SE1505	296	283	102	32	100	47	55	20	2100
40	1 1/2"	SE1506	307	287	116	40	100	103	55	38	4200
50	2"	SE1508	325	277	126	50	119	122	70	55	7100
SINGLE ACTING											
DN	G	AS/4100	A	B	C	D	E	F	Intersect	R _x	Weight
mm		Type	mm	mm	mm	mm	mm	mm	mm	mm	lb
15	1/2"	SE1501	270	107	43	15	15	13	23	5	1000
20	3/4"	SE1502	282	220	77	23	17	45	33	5	1300
25	1"	SE1503	288	229	89	25	17	73	40	10	1600
32	1 1/4"	SE1504	296	283	102	32	100	47	55	20	1900
40	1 1/2"	SE1505	307	287	116	40	100	103	55	38	4000
50	2"	SE1506	320	277	126	50	119	122	70	55	6500



RATED PRESSURE "PN"						
G	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
PN	10	10	10	10	10	10

DOUBLE ACTING											
DN	G	AS/4100	A	B	C	D	E	F	Intersect	R _x	Weight
mm		Type	mm	mm	mm	mm	mm	mm	mm	mm	lb
15	1/2"	SE1502	275	107	43	15	15	13	23	5	1150
20	3/4"	SE1503	282	220	77	23	17	45	33	5	1500
25	1"	SE1504	288	229	89	25	17	73	40	10	1800
32	1 1/4"	SE1505	296	283	102	32	100	47	55	20	2100
40	1 1/2"	SE1506	307	287	116	40	100	103	55	38	4200
50	2"	SE1508	325	277	126	50	119	122	70	55	7100
SINGLE ACTING											
DN	G	AS/4100	A	B	C	D	E	F	Intersect	R _x	Weight
mm		Type	mm	mm	mm	mm	mm	mm	mm	mm	lb
15	1/2"	SE1501	270	107	43	15	15	13	23	5	1000
20	3/4"	SE1502	282	220	77	23	17	45	33	5	1300
25	1"	SE1503	288	229	89	25	17	73	40	10	1600
32	1 1/4"	SE1504	296	283	102	32	100	47	55	20	1900
40	1 1/2"	SE1505	307	287	116	40	100	103	55	38	4000
50	2"	SE1506	320	277	126	50	119	122	70	55	6500



RATED PRESSURE "PN"						
G	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
PN	10	10	10	10	10	10