

EFFEPI RUSTFRI STÅL KUGLEVENTIL TYPE \"AL1\" AISI 316

EFFAL110DA

Kemi rustfri stål kugleventil DN10 double acting
AISI316

- Materiale: Rustfri stål AISI 316
- Medier: Gas, Olie, Væske
- Størrelser: DN10 - DN100 (DA) DN10 - DN50 (SA)
- Fås med pneumatisk aktuator
- Temperaturområde: -15°C - +100°C



PRODUKTBESKRIVELSE

Rustfri stål kugleventil med roterende pneumatisk aktuator.

Ventilkrop: Rustfri stål AISI316

Kugle: Rustfri stål AISI316

Pakning: Virgin PTFE

Temperaturområder:

-15°C - +100°C

Max temperatur for special brug (med fuldt åben ventil):

+100°C brændstofs olier, mineral olier og mageriner

+90°C hav og drikkevand

+60°C trichlorethylen, butan, methan, propan, carbon dioxide

+40°C Alkohol, benzin, lette gasser, naturlige gasser, lime vand, sodavand.

Aktuator tryk:

Double acting fra 3 - 8 bar

Single acting fra 6 - 8 bar

Tilslutninger med GAS ISO228 hun-hun fittings.

Kan leveres med NPT eller DIN tilslutning

GAS tilslutning 1/8"

DA: 3/8" - 1/2" - 3/4" - 1" - 1 1/4" - 1 1/2" - 2" - 2 1/2" - 3" - 4" (double acting)

SANC: 3/8" - 1/2" - 3/4" - 1" - 1 1/4" - 1 1/2" - 2" (single acting normally closed)


SANO: 3/8" - 1/2" - 3/4" - 1" - 1 1/4" - 1 1/2" - 2" (single acting normally open)

Anodiserende behandlet udvendigt i aluminium

DOUBLE ACTING												
DN	G	AS/3/8"	A	B	C	D	E	stroke	F ₁	weight		
mm	Type	mm	mm	mm	mm	mm	mm	mm	kg	lb		
10	3/8"	AS5002	210	95	12	6	43	25	10	22		
15	1/2"	AS5002	270	108	12	7	45	32	20	44		
20	3/4"	AS5002	270	125	12	7	47	38	30	66		
25	1"	AS5002	270	135	12	7	47	45	40	88		
32	1 1/4"	AS6003	280	150	12	8	50	52	60	132		
40	1 1/2"	AS6003	270	165	12	8	50	60	80	176		
50	2"	AS6003	317	175	16	10	60	80	180	396		
65	2 1/2"	AS7004	340	180	18	11	70	100	350	770		
80	3"	AS7005	437	207	18	11	105	130	700	1540		
100	4"	AS7005	437	207	18	11	105	130	700	1540		

SINGLE ACTING (NC-NO)												
DN	G	AS/3/8"	A	B	C	D	E	stroke	F ₁	weight		
mm	Type	mm	mm	mm	mm	mm	mm	mm	kg	lb		
10	3/8"	AS5002	210	95	12	6	43	25	10	22		
15	1/2"	AS5002	270	108	12	7	45	32	20	44		
20	3/4"	AS5002	270	125	12	7	47	38	30	66		
25	1"	AS5002	270	135	12	7	47	45	40	88		
32	1 1/4"	AS6003	280	150	12	8	50	52	60	132		
40	1 1/2"	AS6003	270	165	12	8	50	60	80	176		
50	2"	AS6003	317	175	16	10	60	80	180	396		
65	2 1/2"	AS7004	340	180	18	11	70	100	350	770		
80	3"	AS7005	437	207	18	11	105	130	700	1540		
100	4"	AS7005	437	207	18	11	105	130	700	1540		

OVERALL DIMENSIONS




RATED PRESSURE "PN"												
G	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"		
PN	64	64	64	40	40	40	25	25	25	25		

DOUBLE ACTING												
DN	G	AS/3/8"	A	B	C	D	E	stroke	F ₁	weight		
mm	Type	mm	mm	mm	mm	mm	mm	mm	kg	lb		
10	3/8"	AS5002	210	95	12	6	43	25	10	22		
15	1/2"	AS5002	270	108	12	7	45	32	20	44		
20	3/4"	AS5002	270	125	12	7	47	38	30	66		
25	1"	AS5002	270	135	12	7	47	45	40	88		
32	1 1/4"	AS6003	280	150	12	8	50	52	60	132		
40	1 1/2"	AS6003	270	165	12	8	50	60	80	176		
50	2"	AS6003	317	175	16	10	60	80	180	396		
65	2 1/2"	AS7004	340	180	18	11	70	100	350	770		
80	3"	AS7005	437	207	18	11	105	130	700	1540		
100	4"	AS7005	437	207	18	11	105	130	700	1540		

SINGLE ACTING (NC-NO)												
DN	G	AS/3/8"	A	B	C	D	E	stroke	F ₁	weight		
mm	Type	mm	mm	mm	mm	mm	mm	mm	kg	lb		
10	3/8"	AS5002	210	95	12	6	43	25	10	22		
15	1/2"	AS5002	270	108	12	7	45	32	20	44		
20	3/4"	AS5002	270	125	12	7	47	38	30	66		
25	1"	AS5002	270	135	12	7	47	45	40	88		
32	1 1/4"	AS6003	280	150	12	8	50	52	60	132		
40	1 1/2"	AS6003	270	165	12	8	50	60	80	176		
50	2"	AS6003	317	175	16	10	60	80	180	396		
65	2 1/2"	AS7004	340	180	18	11	70	100	350	770		
80	3"	AS7005	437	207	18	11	105	130	700	1540		
100	4"	AS7005	437	207	18	11	105	130	700	1540		

OVERALL DIMENSIONS



RATED PRESSURE "PN"												
G	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"		
PN	64	64	64	40	40	40	25	25	25	25		