

## EM-243C

### DC-motorstyring

EM-243C  
DC motorstyring 24V, 50A

- 12-48 VDC
- Strømgrænse (1-100 A)
- Rampning
- Digital parameterjustering



#### PRODUKTBESKRIVELSE

#### SPECIFIKATIONER

<b>Brake output</b>	Ja
<b>Change direction of rotation (CW/CCW)</b>	Ja
<b>Control type</b>	Hastighed, Retning, Torque, Softstart/stop
<b>Current limit</b>	1-100
<b>Current limit adjustable</b>	Ja
<b>Currenttrip autoreveice</b>	Ja
<b>Driftstemperatur</b>	-40°C...+60°C
<b>Forsyningsspænding</b>	12-48 V DC
<b>Functions</b>	Currenttrip autoreversing, Brake output, Speed settings, Impulse/continuous mode, Joystick analog input, Softstart/stop, Potentiometer adjustable speed, RS485/Modbus, Stop at limit position, Speedregulator, Change direction of rotation (CW/CCW)
<b>Impulse/continuous mode</b>	Ja
<b>Indstillingsområde</b>	1-100 A
<b>Joystick analog input</b>	Ja
<b>Leverandør</b>	Electromen
<b>Montage</b>	DIN-skinne
<b>Parallel driver four motors</b>	Nej
<b>Parallel driver two motors</b>	Nej
<b>Peak current</b>	(5s) *100

