

## EM-243C

### DC-motorstyring



EM-243C  
DC motorstyring 24V, 50A

- 12-48 VDC
- Strømgrænse (1-100 A)
- Rampning
- Digital parameterjustering



#### PRODUKTBESKRIVELSE

## SPECIFIKATIONER

2053_Current limit (A)	1-100
2421_Peak current (A)	(5s) *100
Brake output	Ja
Change direction of rotation (CW/CCW)	Ja
Control type	Hastighed, Retning, Torque, Softstart/stop
Current limit adjustable	Ja
Currenttrip autoreveice	Ja
Driftstemperatur	-40°C...+60°C
Forsyningsspænding	12-48 V DC
Impulse/continuous mode	Ja
Indstillingsområde	1-100 A
Joystick analog input	Ja
Leverandør	Electromen
Montage	DIN-skinne
Parallel driver four motors	Nej
Parallel driver two motors	Nej
Position with potentiometer	Nej
Positioning	Nej
Potentiometer adjustable speed	Ja

<b>PWM frequency</b>	2kHz/16kHz
<b>RS232</b>	Nej
<b>RS485/Modbus</b>	Nej
<b>Softstart/stop</b>	Ja
<b>Speed settings</b>	Ja
<b>Speedregulator</b>	Ja
<b>Stop at limit position</b>	Ja
<b>Suitable engine</b>	DC
<b>Vægt</b>	190 g

