

INTERAPP PNEUMATISK AKTUATOR

Til butterflyventiler

IA250S08

Pneu. aktuator single act.



- Krop: Aluminium, PTFE coated udvendigt (høj kemisk resistens) Lufttilslutning: Namur eller gevind
- Styretryk: nominelt 6 bar (med mulighed for 2 til 8 bar). Medietemperatur: 20 til 80°C
- Højt drejningsmoment ved start. Udvendig justering af vejstop
- Indikation af on/off Standard i overensstemmelse med ATEX 94/9/EC
- Beskyttelse: Ex II 2 GD Tmax = 95°C



PRODUKTBESKRIVELSE

InterApp's pneumatiske aktuator, IA Motion, kombinerer innovative designfunktioner med den nyeste teknologi, herunder materialer og beskyttelsescoating. Dette resulterer i en aktuator i aller højeste klasse på markedet.

Passer til ISO-top

Kontakt vores produktspecialist, for den mest optimale løsning til netop dit behov

;




Limit switches





Positioner



Proximity switch
AS-Interface



Solenoid valve



Actuator size, solenoid valve and air supply pipe according table below.

Actuator size	Solenoid valve	Air supply pipe
IA045 - 350	≥ DN 4	≥ DN 4
IA400 - 600	≥ DN 7	≥ DN 6
IA650 - 700	≥ DN 12	≥ DN 8
IA750 - 1000	≥ DN 12	≥ DN 10

Product features

- **Function** IA...D double acting
IA...S single acting
- **Nominal torque** 15 + 10007 Nm
(double acting at 6 bar air supply)
- **Supply pressure** 3 - 8 bar (IA1000D 3 - 7 bar)
- **Supply fluids** Filtered air or neutral gas
- **Working temperature** -40°C - 80°C
- **Connection** Mounting face for valves according to EN ISO 5211, for solenoid valves and accessories to VDI/VDE 3845 (NAMUR)
- **Lubrication** Factory lubricated for the life of actuator under normal working conditions
- **ATEX** Actuator IP67, standard in compliance with ATEX 94/9/EC