



FØLER MED GEVIND TIL PLASTINDUSTRIEN

TC47-NT

TC47-NT
Føler med gevind

- Måleområde fra -40 op til 750°C
- Type J, L, K eller T (andre efter behov)
- Forlængerkabel i eksempelvis PTFE, fiberglas eller PVC
- Fikseret forudbestemt længde og monteres direkte i processen
- Meget let at skifte



PRODUKTBESKRIVELSE

SPECIFIKATIONER

Temperaturområde fra	-40 °C
Temperaturområde til	750 °C

																																									
Nozzle bolt material ■ Stainless steel ■ Brass ■ Others on request	Lead wire covering ■ None ■ Stainless steel overbraid (no tracer) ■ Stainless steel overbraid (with tracer) ■ Tin copper overbraid																																								
Junction ■ Grounded (unisolated) ■ Ungrounded (isolated)	Termination at lead end ■ Bare ends 																																								
Nozzle bolt thread size ■ 1/4 x 28 ■ M5 ■ M8 ■ Others on request	 ■ Standard thermo plug 2-pin (male) ■ Miniature thermo plug 2-pin (male) ■ Standard plug with cable clamp (male) ■ Miniature plug with cable clamp (male)																																								
Lead length ■ 500 mm ■ 1000 mm ■ 1500 mm ■ 2000 mm ■ 2500 mm ■ Others on request	 ■ Lemosa plug size 10 (male) ■ Lemosa plug size 25 (male) ■ Screw-in plug, Binder (male) ■ Others on request 																																								
Lead wire ■ Fibreglass / Fibreglass ■ PTFE / PTFE ■ PVC / PVC ■ Kapton / Kapton ■ Others on request	Calibration type <table> <tr> <td>■ J</td><td>ANSI MC96.1</td><td>red Ø</td><td>white Ø</td></tr> <tr> <td>■ K</td><td>ANSI MC96.1</td><td>red Ø</td><td>yellow Ø</td></tr> <tr> <td>■ T</td><td>ANSI MC96.1</td><td>red Ø</td><td>blue Ø</td></tr> <tr> <td>■ J</td><td>IEC 584-3</td><td>white Ø</td><td>black Ø</td></tr> <tr> <td>■ K</td><td>IEC 584-3</td><td>white Ø</td><td>green Ø</td></tr> <tr> <td>■ T</td><td>IEC 584-3</td><td>white Ø</td><td>brown Ø</td></tr> <tr> <td>■ J</td><td>DNV 43714</td><td>blue Ø</td><td>red Ø</td></tr> <tr> <td>■ K</td><td>DNV 43714</td><td>green Ø</td><td>red Ø</td></tr> <tr> <td>■ T</td><td>DNV 43714</td><td>brown Ø</td><td>red Ø</td></tr> <tr> <td colspan="4">■ Others on request</td></tr> </table>	■ J	ANSI MC96.1	red Ø	white Ø	■ K	ANSI MC96.1	red Ø	yellow Ø	■ T	ANSI MC96.1	red Ø	blue Ø	■ J	IEC 584-3	white Ø	black Ø	■ K	IEC 584-3	white Ø	green Ø	■ T	IEC 584-3	white Ø	brown Ø	■ J	DNV 43714	blue Ø	red Ø	■ K	DNV 43714	green Ø	red Ø	■ T	DNV 43714	brown Ø	red Ø	■ Others on request			
■ J	ANSI MC96.1	red Ø	white Ø																																						
■ K	ANSI MC96.1	red Ø	yellow Ø																																						
■ T	ANSI MC96.1	red Ø	blue Ø																																						
■ J	IEC 584-3	white Ø	black Ø																																						
■ K	IEC 584-3	white Ø	green Ø																																						
■ T	IEC 584-3	white Ø	brown Ø																																						
■ J	DNV 43714	blue Ø	red Ø																																						
■ K	DNV 43714	green Ø	red Ø																																						
■ T	DNV 43714	brown Ø	red Ø																																						
■ Others on request																																									