



FØLER MED RINGFÆSTE TIL PLASTINDUSTRIEN

Serie TC47-RL

TC47-RL
Termoelement med ringfæste

- Måleområde fra -40 op til 750 °C
- Type J, L, K, eller T (andre efter behov)
- Ringøje af rustfrit stål
- Forlængerkabel i eksempelvis PTFE, fiberglas eller PVC
- Meget let at installere og skifte ud



PRODUKTBESKRIVELSE

SPECIFIKATIONER

Temperaturområde fra	-40 °C
Temperaturområde til	750 °C

																																									
Ring lug material ■ Stainless steel ■ Nickel clad copper ■ Others on request	Termination at lead end ■ Bare ends ■ Standard thermo plug 2-pin (male) ■ Miniature thermo plug 2-pin (male) ■ Standard plug with cable clamp (male) ■ Miniature plug with cable clamp (male) ■ Lemosa plug size 15 (male) ■ Lemosa plug size 25 (male) ■ Screw-in plug, Binder (male) ■ Others on request																																								
Junction ■ Grounded (unisolated) ■ Ungrounded (isolated)	  																																								
Ring Ø size ■ 4.2 mm ■ 5.2 mm ■ 6.2 mm ■ Others on request																																									
Lead length ■ 500 mm ■ 1000 mm ■ 1500 mm ■ 2000 mm ■ 2500 mm ■ Others on request																																									
Lead wire ■ Fiberglass / Fibreglass ■ PTFE / PTFE ■ PVC / PVC ■ Kapton / Kapton ■ Others on request	Calibration type <table><tr><td>■ J</td><td>ANSI MC96.1</td><td>red Ø</td><td>white Ø</td></tr><tr><td>■ K</td><td>ANSI MC96.1</td><td>red Ø</td><td>yellow Ø</td></tr><tr><td>■ T</td><td>ANSI MC96.1</td><td>red Ø</td><td>blue Ø</td></tr><tr><td>■ J</td><td>IEC 584-3</td><td>white Ø</td><td>black Ø</td></tr><tr><td>■ K</td><td>IEC 584-3</td><td>white Ø</td><td>green Ø</td></tr><tr><td>■ T</td><td>IEC 584-3</td><td>white Ø</td><td>brown Ø</td></tr><tr><td>■ J</td><td>DIN 43714</td><td>blue Ø</td><td>red Ø</td></tr><tr><td>■ K</td><td>DIN 43714</td><td>green Ø</td><td>red Ø</td></tr><tr><td>■ T</td><td>DIN 43714</td><td>brown Ø</td><td>red Ø</td></tr><tr><td colspan="4">■ Others on request</td></tr></table>	■ J	ANSI MC96.1	red Ø	white Ø	■ K	ANSI MC96.1	red Ø	yellow Ø	■ T	ANSI MC96.1	red Ø	blue Ø	■ J	IEC 584-3	white Ø	black Ø	■ K	IEC 584-3	white Ø	green Ø	■ T	IEC 584-3	white Ø	brown Ø	■ J	DIN 43714	blue Ø	red Ø	■ K	DIN 43714	green Ø	red Ø	■ T	DIN 43714	brown Ø	red Ø	■ Others on request			
■ J	ANSI MC96.1	red Ø	white Ø																																						
■ K	ANSI MC96.1	red Ø	yellow Ø																																						
■ T	ANSI MC96.1	red Ø	blue Ø																																						
■ J	IEC 584-3	white Ø	black Ø																																						
■ K	IEC 584-3	white Ø	green Ø																																						
■ T	IEC 584-3	white Ø	brown Ø																																						
■ J	DIN 43714	blue Ø	red Ø																																						
■ K	DIN 43714	green Ø	red Ø																																						
■ T	DIN 43714	brown Ø	red Ø																																						
■ Others on request																																									
Lead wire covering ■ None ■ Stainless steel overbraid (no tracer) ■ Stainless steel overbraid (with tracer) ■ Tin copper overbraid																																									