

SIKKERHEDS PLC FORBEREDT FOR PROCESLÅS

Safety Simplifier E3P M12 fra SSP

SP-N-89-140-23

Safety Simplifier forberedt for Holdx proceslås via M12 konnektor, 14 I/O, 2NO relæudgange, forberedt med nødstop og 3 trukknapper. Til en enhed leveres der to forskruninger med.

- Plug & Play med Holdx processlås
- 14 I/O som sikre ind- eller udgange
- 2 x dobbelte relæudgange
- Sikker trådløs kommunikation
- Forberedt og monteret til brug



PRODUKTBESKRIVELSE

SPECIFIKATIONER

Anbefalet sikring	2,5 A
IP-klasse	IP65
Load Output Max	600 mA
Materiale hus	UL-certificeret materiale, PC + ABS (brandsikker), ANSI/UL 94
Max load in total	2000 mA
Spændingstolerance	10-30V DC
Temperaturområde fra	-20 °C
Temperaturområde til	65 °C
Vægt	0,235 kg



Product tested	Safety PLC unit with radio transceiver	Certificate holder	SSPN Safety System Products North AB Tullkärnsvä 14 430 31 Onsala Sweden
-----------------------	--	---------------------------	--

Type designation Safety Simplifier (sxyyzz)
xx = 00-15, 20-22, 40-42
yy = L.D., P.D., CA
zz = 00, 02, 20, 21

Codes and standards	ISO 13849-1:2015 IEC 61508 Parts 1-7:2010	IEC 61000-6-7:2014
---------------------	--	--------------------

Intended application The Safety Simplifier complies with the requirements of Cat. 4 / PL e acc. to ISO 13849-1, SIL 3 acc. to IEC 61508 and can be used in applications up to PL e and SIL 3.

Specific requirements	The instructions of the associated Installation, Operating and Safety Manual shall be considered.
------------------------------	---

It is confirmed, that the product tested complies with the requirements for machines defined in Annex I of the EC Directive 2006/42/EC.

Valid until 2025-11-19

The issue of this certificate is based upon an examination where results are documented in Report No. 969/F3P/17/03/018 issued 2018-04-04.
This certificate is valid only for products which are certified under the protocol tested.

ASRA 2019-11-18

www.fs-products.com
www.fuv.com

