

SIKKERHEDS PLC MED TREPUNKTS-HÅNDTAG

Safety Simplifier fra SSP

SP-N-89-160-129

- Plug & Play med Zeus 3punkt håndtag
- 14 I/O som sikre ind- eller udgange
- 2 x dobbelte relæudgange
- Sikker trådløs kommunikation



PRODUKTBESKRIVELSE

SPECIFIKATIONER

Anbefalet sikring	2,5 A
IP-klasse	IP65
Load Output Max	600 mA
Materiale hus	UL-certificeret materiale, PC + ABS (brandsikker), ANSI/UL 94
Max load in total	2000 mA
Spændingstolerance	10-30V DC
Temperaturområde fra	-20 °C
Temperaturområde til	65 °C
Vægt	0,235 kg

EC Type-Examination Certificate

Reg.-No.: 01/205/5692/00/18

Product tested	Safety PLC unit with radio transceiver	Certificate holder	SSPM Safety System Produktions-Norm AB Tullkvarnsvägen 14 428 31 Onsala Sweden
Type designation	Safety Simplifier Safety22 xx = 00-18, 20-23, 40-43 yy = L3, R3, CA zz = 00, 02, 20, 21		
Codes and standards	ISO 13849-1:2015 IEC 61508 Parts 1-7:2010	IEC 61000-6-7:2014	
Intended application	The Safety Simplifier complies with the requirements of Cat. 4 (PL a acc. to ISO 13849-1, SIL 3 acc. to IEC 61508) and can be used in applications up to PL a and SIL 3.		
Specific requirements	The instructions of the associated Installation, Operating and Safety Manual shall be considered.		

It is confirmed, that the product tested complies with the requirements for machines defined in Annex I of the EC Directive 2006/42/EC.
Valid until 2025-11-19

The issue of this certificate is based upon an examination whose results are documented in Report No. 9634/SP-17/19/2018 dated 2019-1-1-2019.
This certificate is valid only for products which are identified by the product tested.

Notified Body for Machinery, No. 0035

TÜVRheinland
Precision Right.



