

OVERALL DIMENSIONS

DOUBLE ACTING

DN	G	40/50/60	A	B	C	D	E	F	Pressure bar	Max. weight
10	1/2"	560/582	225	206	80	73	45	27	4	1820
15	3/4"	560/582	225	206	80	73	45	27	4	560
20	1"	560/582	225	206	80	73	45	27	4	2350
25	1 1/4"	560/582	225	206	80	73	45	27	4	2350
32	1 1/2"	560/582	225	206	80	73	45	27	4	2350
40	1 3/4"	560/582	225	206	80	73	45	27	4	2350
50	2"	560/582	225	206	80	73	45	27	4	2350
63	2 1/4"	560/582	225	206	80	73	45	27	4	2350
80	2 1/2"	560/582	225	206	80	73	45	27	4	2350
100	3"	560/582	225	206	80	73	45	27	4	2350
125	3 1/2"	560/582	225	206	80	73	45	27	4	2350
150	4"	560/582	225	206	80	73	45	27	4	2350

SINGLE ACTING

DN	G	40/50/60	A	B	C	D	E	F	Pressure bar	Max. weight
10	1/2"	560/582	225	206	80	73	45	27	4	1820
15	3/4"	560/582	225	206	80	73	45	27	4	560
20	1"	560/582	225	206	80	73	45	27	4	2350
25	1 1/4"	560/582	225	206	80	73	45	27	4	2350
32	1 1/2"	560/582	225	206	80	73	45	27	4	2350
40	1 3/4"	560/582	225	206	80	73	45	27	4	2350
50	2"	560/582	225	206	80	73	45	27	4	2350
63	2 1/4"	560/582	225	206	80	73	45	27	4	2350
80	2 1/2"	560/582	225	206	80	73	45	27	4	2350
100	3"	560/582	225	206	80	73	45	27	4	2350
125	3 1/2"	560/582	225	206	80	73	45	27	4	2350
150	4"	560/582	225	206	80	73	45	27	4	2350

The image shows two technical drawings of hydraulic cylinders. The top drawing is labeled 'DOUBLE ACTING' and the bottom drawing is labeled 'SINGLE ACTING'. Both drawings show the cylinder in two views: a side view and a front view. The side view shows the cylinder with dimensions A, B, C, D, E, F, and G. The front view shows the cylinder with dimensions A, B, C, D, E, F, and G. The drawing also includes a detail of the cylinder head with dimensions A, B, C, D, E, F, and G. The drawing is labeled 'DOUBLE ACTING' and 'SINGLE ACTING'.