

EFFEPI RUSTFRI STÅL KUGLEVENTILER TYPE "AL" AISI 304

EFFAL10DA

Kemi rustfri stål kugleventil DN10 double acting
AISI304

- Materiale: Rustfri stål AISI 304
- Medier: Gas, Olie, Væske
- Størrelser: DN10 - DN100 (DA) DN10 - DN50 (SA)
- Fås med pneumatisk aktuator
- Temperaturområde: -15°C - +100°C



PRODUKTBESKRIVELSE

Rustfri stål kugleventil med roterende pneumatisk aktuator.

Ventilkrop: Rustfri stål AISI304

Kugle: Rustfri stål AISI304

Pakning: Virgin PTFE

Temperaturområder:

-15°C - +100°C

Max temperatur for special brug (med fuldt åben ventil):

+100°C brændstofs olier, mineral olier og mageriner

+90°C hav og drikkevand

+60°C trichlorethylen, butan, methan, propan, carbon dioxide

+40°C Alkohol, benzin, lette gasser, naturlige gasser, lime vand, sodavand.

Aktuator tryk:

Double acting fra 3 - 8 bar

Single acting fra 6 - 8 bar

Tilslutninger med GAS ISO228 hun-hun fittings.

Kan leveres med NPT eller DIN tilslutning

GAS tilslutning 1/8"

DA: 3/8" - 1/2" - 3/4" - 1" - 1 1/4" - 1 1/2" - 2" - 2 1/2" - 3" - 4" (double acting)

SANC: 3/8" - 1/2" - 3/4" - 1" - 1 1/4" - 1 1/2" - 2" (single acting normally closed)


SANO: 3/8" - 1/2" - 3/4" - 1" - 1 1/4" - 1 1/2" - 2" (single acting normally open)

Anodiserende behandlet udvendigt i aluminium

DOUBLE ACTING											
DN	G	40/38	A	B	C	D	E	mm	F ₁	Weight	
mm	Type	mm	mm	mm	mm	mm	mm	mm	mm	kg	lb
10	3/8"	SP502	210	70	12	40	45	25	10	150	
15	1/2"	SP502	270	90	12	50	65	32	20	200	
20	1"	SP502	330	110	12	60	80	40	15	300	
25	1 1/4"	SP502	390	130	12	70	100	50	10	450	
32	1 1/2"	SP502	450	150	12	80	120	60	8	600	
40	2"	SP502	510	170	12	90	140	70	6	800	
50	2 1/2"	SP502	570	190	12	100	160	80	5	1100	
60	3"	SP502	630	210	12	110	180	90	4	1500	
80	4"	SP502	750	250	12	130	220	110	3	2200	
100	5"	SP502	870	290	12	150	260	130	2	3100	

SINGLE ACTING (NC+NO)											
DN	G	40/38	A	B	C	D	E	mm	F ₁	Weight	
mm	Type	mm	mm	mm	mm	mm	mm	mm	mm	kg	lb
10	3/8"	SP502	210	70	12	40	45	25	10	150	
15	1/2"	SP502	270	90	12	50	65	32	20	200	
20	1"	SP502	330	110	12	60	80	40	15	300	
25	1 1/4"	SP502	390	130	12	70	100	50	10	450	
32	1 1/2"	SP502	450	150	12	80	120	60	8	600	
40	2"	SP502	510	170	12	90	140	70	6	800	
50	2 1/2"	SP502	570	190	12	100	160	80	5	1100	
60	3"	SP502	630	210	12	110	180	90	4	1500	
80	4"	SP502	750	250	12	130	220	110	3	2200	
100	5"	SP502	870	290	12	150	260	130	2	3100	

OVERALL DIMENSIONS



RATED PRESSURE "PN"									
G	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"
PN	64	64	64	40	40	40	25	25	25