

SPRING LOADED, DIAPHRAGM SENSOR, SUB-ATMOFERISK

DV Serien Backpressure regulator

DV
DV Serien

- Controlled Pressure Range: 760 - 50 mm Hg absolute
- Design Proof Pressure: 150% of maximum operating
- Leakage: Bubble-tight
- Operating Temperatures: Buna-N: -40°F to 165°F / -40°C to 74°C - Ethylene Propylene: -40°F to 250°F / -40°C to 121°C - Viton®: -15°F to 165°F / -26°C to 74°C
- CV: 0.25



PRODUKT BESKRIVELSE

TESCOM DV Series

En kompakt, letvægts, diaphragm regulator som tilbyder vacuum kontrol op til 0.1% Nøjagtighed. Med mulighed for konstant bleed feature som giver mulighed for trykjustering begge veje.

Applikationer

- Instrumentation testing
- Calibration equipment

Fordele

- Kontrollere sub-atmospheric pressure
- Excellent repeatability
- Nøjagtig diaphragm-type regulering $\pm 0.1\%$ af full scale
- Høj nøjagtighed på 10 mm Hg absolute opnås ved konstant bleed option
- Nem at vedligeholde
- Lav operating handknob torque
- Mulighed for Captured bonnet og panel mounting



