

VM-SERIEN  
VM-Serien

- 

## Tescom VM Serien

## Applikationer

- ## Fordele

- Example for selecting a part number:

| VVM 6                                |                         |                  |                  |                                 | VV                              |                           | 2               |                  | 12               |                 | 2                |                 |
|--------------------------------------|-------------------------|------------------|------------------|---------------------------------|---------------------------------|---------------------------|-----------------|------------------|------------------|-----------------|------------------|-----------------|
| Example for selecting a part number: |                         |                  |                  |                                 |                                 |                           |                 |                  |                  |                 |                  |                 |
| BASIC SERIES                         | BODY AND TRIM MATERIAL  | SEAT MATERIAL    | O-RING MATERIAL  | MAXIMUM OPERATING PRESSURE      | OPERATING TEMPERATURES          |                           | INLET PORT SIZE | OUTLET PORT SIZE | OUTLET PORT SIZE | INLET PORT SIZE | OUTLET PORT SIZE | INLET PORT SIZE |
| VVM                                  | 6 - 115 Stainless Steel | Polypropylene    | VM - NBR, Buna-N | 0.0003 gpm (2.04 L/min)         | 400 to 1070 psi (20 to 120 bar) | 1 - 500 psi (7 to 35 bar) | 1 - 5/8"        | 12 - 1/2"        | 12 - 1/2"        | 12 - 1/2"       | 12 - 1/2"        | 2 - 1/8"        |
|                                      |                         | VM - NBR, Buna-N | VM - NBR, Buna-N | 400 to 1070 psi (20 to 120 bar) | 1 - 500 psi (7 to 35 bar)       | 1 - 500 psi (7 to 35 bar) | 1 - 5/8"        | 12 - 1/2"        | 12 - 1/2"        | 12 - 1/2"       | 12 - 1/2"        | 2 - 1/8"        |
|                                      |                         | VM - FKM         | VM - FKM         | 400 to 1070 psi (20 to 120 bar) | 1 - 500 psi (7 to 35 bar)       | 1 - 500 psi (7 to 35 bar) | 1 - 5/8"        | 12 - 1/2"        | 12 - 1/2"        | 12 - 1/2"       | 12 - 1/2"        | 2 - 1/8"        |
|                                      |                         | VM - EPDM        | VM - EPDM        | 400 to 1070 psi (20 to 120 bar) | 1 - 500 psi (7 to 35 bar)       | 1 - 500 psi (7 to 35 bar) | 1 - 5/8"        | 12 - 1/2"        | 12 - 1/2"        | 12 - 1/2"       | 12 - 1/2"        | 2 - 1/8"        |
|                                      |                         | VM - LSR         | VM - LSR         | 400 to 1070 psi (20 to 120 bar) | 1 - 500 psi (7 to 35 bar)       | 1 - 500 psi (7 to 35 bar) | 1 - 5/8"        | 12 - 1/2"        | 12 - 1/2"        | 12 - 1/2"       | 12 - 1/2"        | 2 - 1/8"        |

