

KEMISK INJECTION, SPRING LOADED, PISTON SENSOR

56-2000 Serien Trykreducerede regulator

56-2000
56-2000 serien

- Max indgangstryk: 1034 bar
- Max udgangstryk: 1034 bar
- Temperaturområde: -26 til 74°C
- CV: 0.06, 0.12
- Leak: Bubble-tight



PRODUKTBESKRIVELSE

Tescom 56-2000 Serien

Denne serie giver dig et meget nøjagtigt flow kontrol, som giver dig mulighed for at have et kontinuerligt injection rate over the life of the well.

Applikationer

- Offshore Chemical Injection

Fordele

Nøjagtigt og kontinuerligt flow kontrol som reducere riskoen for flowtab fra under og efter injection

Høj kvalitets piston-sensor komponenter som giver forlænget levetid i offshore applikationer og som reducere vedligeholdelse og unødigt downtime


Alternativ muligheder for fuld automatisk injection rate kontrol med ER5000

Example for selecting a part number:

56-20	8	0	D	6	9	D	2	7	0	
BASIC SERIES	MAXIMUM INLET PRESSURE (BODY MATERIAL)	MAXIMUM OUTLET PRESSURE (SPRING/SEAL MATERIAL)	SOFT GOOD MATERIAL	STATIC O-RINGS	BACK-UP RINGS	INLET AND OUTLET PORT TYPE	INLET AND OUTLET PORT SIZE	FLOW CAPACITY	MAIN VALVE AND VENT SEAT	GAUGE PORT OPTIONS
56-20	8 - 15,000 psig 1034 bar (17.4 MPa)	8 - 200 15,000 psig 11.8 1034 bar (103.4 MPa)	8 - Nitrile, Buna-N	Nitrile, Buna-N	PS 111	8 - Medium Pressure	1/2 - 1/2"	2 - C ₁ = 0.06 3 - C ₁ = 0.12	Z - Single SP1	8 - No gauge ports

1. Pressure at which regulator is used must be compatible with the pressure rating of the port and seal type provided.

1. Pressure at which regulator is used must be compatible with the pressure rating of the regulator and part size/type provided.



All dimensions are reference & nominal
Metric (in brackets) equivalents are in brackets