

FØLERE TIL FASTSPÆNDING, TIL PLASTINDUSTRIEN

Serie TC47-UB

TC47-UB

Termoelement til fastspænding

- Måleområde fra -40 op til 750 °C
- Type J, L K eller T (andre efter behov)
- Sensorplatte av rustfrit stål
- Formbart sensorelement
- Meget let at installere og skifte ud



PRODUKTBESKRIVELSE

SPECIFIKATIONER

Temperaturområde fra	-40 °C
Temperaturområde til	750 °C

Under the band ■ Stainless steel	Termination at lead end ■ Bare ends ■ Standard thermo plug 2-pin (male) ■ Miniature thermo plug 2-pin (male)	
Junction ■ Grounded (unisolated)	■ Standard plug with cable clamp (male) ■ Miniature plug with cable clamp (male)	
Shim tab size ■ 3/4" x 3/4" (0.020" thickness) (19 x 19 mm)	■ Lemosa plug size 1S (male) ■ Lemosa plug size 2S (male)	
Lead length ■ 500 mm ■ 1000 mm ■ 1500 mm ■ 2000 mm ■ 2500 mm ■ Others on request	■ Screw-in plug, Binder (male) ■ Others on request	
Lead wire ■ Fibreglass / Fibreglass ■ PTFE / PTFE ■ PVC / PVC ■ Kapton / Kapton ■ Others on request	Calibration type ■ J ANSI MC96.1 red Ø white Ø ■ K ANSI MC96.1 red Ø yellow Ø ■ T ANSI MC96.1 red Ø blue Ø ■ J IEC 584-3 white Ø black Ø ■ K IEC 584-3 white Ø green Ø ■ T IEC 584-3 white Ø brown Ø ■ J DIN 43714 blue Ø red Ø ■ K DIN 43714 green Ø red Ø ■ T DIN 43714 brown Ø red Ø ■ Others on request	
Lead wire covering ■ None ■ Stainless steel overbraid (no tracer) ■ Stainless steel overbraid (with tracer) ■ Tin copper overbraid		

Under the band ■ Stainless steel	Termination at lead end ■ Bare ends ■ Standard thermo plug 2-pin (male) ■ Miniature thermo plug 2-pin (male)	
Junction ■ Grounded (unisolated)	■ Standard plug with cable clamp (male) ■ Miniature plug with cable clamp (male)	
Shim tab size ■ 3/4" x 3/4" (0.020" thickness) (19 x 19 mm)	■ Lemosa plug size 1S (male) ■ Lemosa plug size 2S (male)	
Lead length ■ 500 mm ■ 1000 mm ■ 1500 mm ■ 2000 mm ■ 2500 mm ■ Others on request	■ Screw-in plug, Binder (male) ■ Others on request	
Lead wire ■ Fibreglass / Fibreglass ■ PTFE / PTFE ■ PVC / PVC ■ Kapton / Kapton ■ Others on request	Calibration type ■ J ANSI MC96.1 red Ø white Ø ■ K ANSI MC96.1 red Ø yellow Ø ■ T ANSI MC96.1 red Ø blue Ø ■ J IEC 584-3 white Ø black Ø ■ K IEC 584-3 white Ø green Ø ■ T IEC 584-3 white Ø brown Ø ■ J DIN 43714 blue Ø red Ø ■ K DIN 43714 green Ø red Ø ■ T DIN 43714 brown Ø red Ø ■ Others on request	
Lead wire covering ■ None ■ Stainless steel overbraid (no tracer) ■ Stainless steel overbraid (with tracer) ■ Tin copper overbraid		