







the pressure vessel has to be calculated for
adequate reinforcement at its particular size ("D")

categorie: IV
module: G
test pressure see enclosure
marks acc. appandix I No. 3.3. PED

max. working pressure: +4/-1bar/FV
max. working temperature: +200°C

execution of the weldingprocedures by examined welders
with a testet filler metal (TÜV/ASME)
weldingdetails according to drawing No.: 1001

material test reports for pressure frequented parts:
plate: 3.1/EN10204 AD-W2 (W10) / ASME
flange: 3.1/EN10204 AD-W2 (W9) / ASME

safe load implementation of joint components position 11-17
acc. to techn. report No.: WB-M-960127121 attachment with
drawing No.: 200 00 02
cutting test and non-destructive test acc. to AD
- instructions HP 5/2 and 5/3

Pos.	Anz.	Benennung	Material	WAZ EN10204	Z.-Nr.
17	6	bolt ø16mm	1.4301	3.1 AD-W2	2019
16	12	butt strap 6mm	1.4301	3.1 AD-W2	2018
15	12	circlip ø16mm	1.4122		2019
14	6	screw M16x125mm	A4-70	3.1 AD-W2	2015 125
13	6	sleeve ø40mm	1.4301	3.1 AD-W2	2017
12	6	washer	1.4301		
11	6	plastic handle M16	1.4301/Duropl.	3.1 AD-W2	2016
10	1	handle ø8mm	1.4301	2.2	2021
9	1	hinge	1.4301	2.2	
8	1	circlip ø12mm	1.4122		2013
7	2	hinge butt strap 6mm	1.4301	2.2	2025k
6	1	bolt ø12mm	1.4301	2.2	2013
5	1	gasket ø307xø8mm	Silikon		Standard
4	1	neck 126x4mm	1.4571	3.1 AD-W2	
3	1	neck flange	1.4571	3.1 AD-W2	
2	1	cover R~500x5mm	1.4571	3.1 AD-W2	
1	1	cover flange	1.4571	3.1 AD-W2	

ZfP/NDE:	none
Zusatzwerkstoff/filler metal:	1.4430
Schweißverfahren/welding procedure:	PAW/GTAW/SAW
Schweißnahtausnutzung/Joint efficiency	0,85

zimmerlin
EDELSTAHL-TECHNIK GMBH
Verschlüsse und Zubehör aus Edelstahl
für den Behälter- und Anlagenbau
Frohnstettenstraße 19
79268 Bötzingen
Tel: 0049-(0)7663/6088-0
Fax: 0049-(0)7663/6088-88
info@zimmerlin.de
www.zimmerlin.de

	Datum	Name
Bearb.	15.06.2010	Schäfer
Gepr.		
Norm		

The copyright of these drawings and all enclosures remains with us. They are only for personal use for the creation. It is not allowed to copy or duplicate them without our written consent.

M:\DW\1\00\Standard\NW300\23082506 engl.dwg

Allgemeintoleranzen	DIN ISO 2768 m
Werkstoff (Mediumberührt):	1.4571
Maßstab	1:2
zul. Betriebs-Temp:	250°C
zul. Betriebs-Ü-Druck:	+8/-1 bar

pressure dome cover NW300

23082506 engl