

Product data

for design verification according to IEC / EN 61439-1

Product description

Part No.	33701
Product name	in-line fuse switch-disconnector 250 A
Description	size 1, 3-pole switchable screw M12 for busbars 30, 40, 60, 80, 100, 120 x 10
Rated current (IEC)	250 A
rated voltage (IEC) AC	800 V
power dissipation at full load of the item	24.0 W
front degree of protection	IP20
type number	QU185-1

Product features for design verification

Construction

10.2	Strength of materials and parts	see following subitems
10.2.2	Resistance to corrosion	Requirements fulfilled Wöhner products are electrical equipment for which the respective product standard is to be applied. The single parts made out of ferrous metals are protected efficiently against corrosion.
10.2.3	Properties of insulating materials	see following subitems
10.2.3.1	Verification of thermal stability of enclosures	Wöhner products do not represent an enclosure. However, the required heat resistance of 70° is fulfilled.
10.2.3.2	Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects	Requirements fulfilled (glow wire test) parts necessary to retain current carrying parts in position: 960°C other parts: 650 °C
10.2.4	Resistance to ultra-violet (UV) radiation	only applicable for outdoor installations not relevant, since Wöhner components are generally not used as external parts
10.2.5	Lifting	not relevant, since the whole assembly must be evaluated
10.2.6	Mechanical impact	not relevant, only applicable for enclosures
10.2.7	Marking	requirements fulfilled
10.3	Degree of protection of enclosures	not relevant, only applicable for enclosures
10.4	Clearances and creepage distances	the requirements are fulfilled for the single Wöhner components
10.5	Protection against electric shock and integrity of protective circuits	lies within the responsibility of the assembler
10.6	Incorporation of switching devices and components	lies within the responsibility of the panel builder the requirements are fulfilled for the single Wöhner components, as long as they are used as intended and Wöhner's mounting and operating instructions are respected
10.7	Internal electrical circuits and connections	lies within the responsibility of the panel builder the requirements are fulfilled for the single Wöhner components, as long as they are used as intended and Wöhner's mounting and operating instructions are respected

10.8 Terminals for external conductors

lies within the responsibility of the panel builder
the requirements are fulfilled for the single Wöhner components, as long as they are used as intended and Wöhner's mounting and operating instructions are respected

Behaviour

10.9 Dielectric properties

see following subitems

10.9.1 General

lies within the responsibility of the panel builder
the requirements are fulfilled for the single Wöhner components, as long as they are used as intended and Wöhner's mounting and operating instructions are respected

10.9.2 Power-frequency withstand voltage

1000 V

10.9.3 Impulse withstand voltage

12 kV

10.9.4 Testing of enclosures made of insulating material

not relevant, since the whole assembly must be evaluated

10.9.5 External conditions of insulating material

not relevant

10.10 Verification of temperature rise

the single Wöhner components meet the temperature rise requirements of the the product standards as long as they are used as intended.
Additionally, evidence must be provided for the switchgear combination or for parts of it. Power dissipations of the Wöhner components can be used here.

10.11 Short-circuit withstand strength

cond. short-circuit current with fuses (AC):
50 kA / 800 V (160 A)
cond. short-circuit current with fuses -2-:
100 kA / 690 V (250 A)
cond. short-circuit current with fuses -3-:
120 kA / 500 V (250 A)
approved wth fuse links of operation class:
gG

10.12 Electromagnetic compatibility (EMC)

lies within the responsibility of the assembler

10.13 Mechanical operation

lies within the responsibility of the panel builder
the requirements are fulfilled for the single Wöhner components, as long as they are used as intended and Wöhner's mounting and operating instructions are respected

For further information see: <https://www.woehner.de/en/products/33701.html>