

## Product data

### for design verification according to IEC / EN 61439-1

#### Product description

Part No.	31950
Product name	D-fuse base, busbar mounted, 42mm
Description	touch protected, screw-in gauge ring E 27 / 3P for busbars 12, 15, 20, 25, 30 x 5, 10 and section busbars
Rated current (IEC)	25 A
rated voltage (IEC) AC	500 V
rated voltage (IEC) DC	500 V
power dissipation at full load of the item	1.2 W

#### Product features for design verification

##### Construction

10.2	Strength of materials and parts	see following subitems
10.2.2	Resistance to corrosion	Requirements fulfilled Wöhner products are electrical equipment for which the respective product standard is to be applied. The single parts made out of ferrous metals are protected efficiently against corrosion.
10.2.3	Properties of insulating materials	see following subitems
10.2.3.1	Verification of thermal stability of enclosures	Wöhner products do not represent an enclosure. However, the required heat resistance of 70° is fulfilled.
10.2.3.2	Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects	Requirements fulfilled (glow wire test) parts necessary to retain current carrying parts in position: 960°C other parts: 650 °C
10.2.4	Resistance to ultra-violet (UV) radiation	only applicable for outdoor installations not relevant, since Wöhner components are generally not used as external parts
10.2.5	Lifting	not relevant, since the whole assembly must be evaluated
10.2.6	Mechanical impact	not relevant, only applicable for enclosures
10.2.7	Marking	requirements fulfilled
10.3	Degree of protection of enclosures	not relevant, only applicable for enclosures
10.4	Clearances and creepage distances	the requirements are fulfilled for the single Wöhner components
10.5	Protection against electric shock and integrity of protective circuits	lies within the responsibility of the assembler
10.6	Incorporation of switching devices and components	lies within the responsibility of the panel builder the requirements are fulfilled for the single Wöhner components, as long as they are used as intended and Wöhner's mounting and operating instructions are respected
10.7	Internal electrical circuits and connections	lies within the responsibility of the panel builder the requirements are fulfilled for the single Wöhner components, as long as they are used as intended and Wöhner's mounting and operating instructions are respected

10.8 Terminals for external conductors

lies within the responsibility of the panel builder  
the requirements are fulfilled for the single Wöhner  
components, as long as they are used as intended and  
Wöhner's mounting and operating instructions are  
respected

---

**Behaviour**

---

10.9 Dielectric properties

---

see following subitems

---

10.9.1 General

---

lies within the responsibility of the panel builder  
the requirements are fulfilled for the single Wöhner  
components, as long as they are used as intended and  
Wöhner's mounting and operating instructions are  
respected

---

10.9.2 Power-frequency withstand voltage

---

10.9.3 Impulse withstand voltage

---

4 kV

---

10.9.4 Testing of enclosures made of insulating  
material

---

not relevant, since the whole assembly must be  
evaluated

---

10.9.5 External conditions of insulating material

---

not relevant

---

10.10 Verification of temperature rise

---

the single Wöhner components meet the temperature  
rise requirements of the the product standards as long as  
they are used as intended.  
Additionally, evidence must be provided for the  
switchgear combination or for parts of it. Power  
dissipations of the Wöhner components can be used  
here.

---

10.11 Short-circuit withstand strength

---

short-circuit strength when protected by fuses:  
50 kA  
approved wth fuse links of operation class:  
gG

---

10.12 Electromagnetic compatibility (EMC)

---

lies within the responsibility of the assembler

---

10.13 Mechanical operation

---

lies within the responsibility of the panel builder  
the requirements are fulfilled for the single Wöhner  
components, as long as they are used as intended and  
Wöhner's mounting and operating instructions are  
respected

---

For further information see: <http://www.woehner.de/en/products/31950.html>